# Drake® Two-Piece Toilet, 1.28 GPF, 10" Rough-In

#### **FEATURES**

- TORNADO FLUSH® system, high-efficiency (1.28 GPF/4.8 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces.
- Elongated front bowl, seat sold separately
- Universal Height
- Chrome plated trip lever
- 10" Rough-in, supply line sold separately

#### **MODELS**

- CST776CEFG.10 (#01)
   With CEFIONTECT ceramic glaze without seat
- CST776CEFRG.10 (#01)
   Same as CST776CEFG.10 except right hand trip lever

#### **COMPONENTS**

- C776CEFG.10
   Elongated bowl with CEFIONTECT
- ST776EA
   Tank and cover only
- ST776ER
  Tank and cover only with right-hand trip lever

# **OPTIONAL COMPONENTS**

- THU808(#01, #03, #11, #12, #51, #PN, #BN, #RB)-A
   Trip Lever Cotton, Bone, Colonial White, Sedona

   Beige, Ebony, Polished Nickel, Brushed Nickel, Oil Rubbed Bronze)
- THU820#01-A
   Right Hand Trip Lever Cotton
- ST776EB#01 Tank and Bolt-down Lid (#01 only)

#### **COLORS/FINISHES**

#01 Cotton







#### PRODUCT SPECIFICATION

The two-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF/4.8 LPF. Toilet shall be 10" rough-in. Toilet shall have CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with Polished Chrome trip lever. Toilet shall be TOTO Model CST776CEF\_\_\_G.10#01

#### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC®), EPA WaterSense, State of Massachusetts, City of Los Angeles, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements







# Drake® Two-Piece Toilet, 1.28 GPF, 10" Rough-In


#### **SPECIFICATIONS**

Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	9" x 6-7/8"
Trap Diameter	2-1/8"
Rough-in	10"
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	C776CEFG.10 62 lbs. ST776EA 32 lbs.
Shipping Dimensions	C776CEFG.10 30-1/8" L×15-1/4" W1×10-7/8" W2×17-3/4" H ST776EA 18-3/4" L×8-7/8" W×16-1/4" H

# **INSTALLATION NOTES**


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 10" rough-in distance.

# **DIMENSIONS**





These dimensions and specifications are subject to change without notice