

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au

Dy-Mark LANDSCAPE CHALK



Dy-Mark Landscape Chalk features a fast dry formula, ideal for TEMPORARY marking on roads, pavement, gravel, grass and other areas. Lasts up to 30 days and can be washed off with water. **Landscape Chalk** is suitable for use with the **Long Arm Handle** and **2-Wheel Spot Marking Handle**, also available from Dy-Mark.

DIRECTIONS FOR USE

Suitable Surfaces:

Concrete, bitumen, steel, timber and grass.

Ideal Application Temperature:

Between 5°C and 40°C. Avoid use in windy conditions.

Before Spraying:

Shake can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use.

Application:

Hold can in the **INVERTED** position (upside down), approximately 10-15cm from the surface. Spray width can be adjusted by moving closer or further from the surface to be sprayed.

Drying Time:

Touch dry in 10 minutes (25°C).

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

After Spraying:

Prevent blocking by holding the can **UPRIGHT** and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean.

Removal:

Landscape Chalk can be removed with the use of water, detergent and a stiff brush or high pressure hose. On fresh bitumen or other porous surfaces, removal may be hampered due to solvent/ pigment penetration.

Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



TECHNICAL DATA

Size:	350g Aerosol
Colour:	Yellow and White
Finish:	Matt
Consistency:	Liquid
Propellant:	Hydrocarbon / Dimethyl Ether

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in a well ventilated place.

DISPOSAL

Dispose of contents/container according to regional regulations.

FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available for download from our website www.dymark.com.au or from following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.