# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 20.01.2020 100000027332 Date of first issue: 20.01.2020

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Sikafloor®-169 Part A

Product code : 100000027332

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45
Telefax : +61 2 9725 33 30
Emergency telephone num- : +61 1800 033 111

ber

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

**GHS** label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 20.01.2020 100000027332 Date of first issue: 20.01.2020

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin);	25068-38-6	>= 60 -<= 100
epoxy resin (number average molecular weight		
≤ 700)		
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	>= 1 -< 10
benzyl alcohol	100-51-6	< 10

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 20.01.2020 100000027332 Date of first issue: 20.01.2020

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects

Allergic reactions

**Excessive lachrymation** 

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : •3Z

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

20.01.2020 100000027332 Date of first issue: 20.01.2020 1.0

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection No special measures required.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

20.01.2020 100000027332 Date of first issue: 20.01.2020 1.0

chemical products if a risk assessment indicates this is nec-

essary.

Eye protection Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** liquid

Colour clear

Odour epoxy-like

Odour Threshold No data available

Not applicable рΗ

Melting point/range / Freezing :

No data available

Boiling point/boiling range No data available

Flash point : > 101 °C (214 °F)

(Method: closed cup)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure : 0.07 hPa

Relative vapour density No data available

Density ca. 1.12 g/cm3 (20 °C (68 °F))

Solubility(ies)

No data available Water solubility

Solubility in other solvents No data available

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

20.01.2020 100000027332 Date of first issue: 20.01.2020 1.0

Partition coefficient: n-

octanol/water

: No data available

No data available Auto-ignition temperature

Decomposition temperature No data available

Viscosity

Viscosity, dynamic : ca. 2,000 mPa.s (20 °C (68 °F))

> 20.5 mm2/s ( 40 °C (104 °F)) Viscosity, kinematic

Explosive properties No data available

No data available Oxidizing properties

: Directive 2010/75/EU of 24 November 2010 on industrial Volatile organic compounds

> emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 7.82 %

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Possibility of hazardous reac- : Stable under recommended storage conditions.

Conditions to avoid No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified based on available information.

### **Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

: LD50 Oral (Rat): > 5,000 mg/kg Acute oral toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

# Sikafloor®-169 Part A



Revision Date: Version SDS Number: Date of last issue: -

20.01.2020 100000027332 Date of first issue: 20.01.2020 1.0

Test atmosphere: dust/mist

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

#### **Chronic toxicity**

## Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

## STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

## **Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

20.01.2020 100000027332 Date of first issue: 20.01.2020 1.0

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

**IATA-DGR** 

UN/ID No. UN 3082

Environmentally hazardous substance, liquid, n.o.s. Proper shipping name

(epoxy resin)

Class Ш Packing group

Miscellaneous Labels

Packing instruction (cargo

aircraft)

Packing instruction (passen-

964

964

ger aircraft)

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 20.01.2020 100000027332 Date of first issue: 20.01.2020

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**National Regulations** 

**ADG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
Hazchem Code : •3Z

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 6

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

Prohibition/Licensing Requirements : There is no applicable prohibition or

notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory

legislation.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

# Sikafloor®-169 Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 20.01.2020 100000027332 Date of first issue: 20.01.2020

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 20.01.2020

Date format : dd.mm.yyyy

#### Full text of other abbreviations

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN