



Biometrics

RFID

Barcode

QR Code

# Qualica-RD CAPELLA 8000

Rotary turnstile with glass blade designed for access control.

**Qualica-RD CAPELLA 8000.** This turnstile has a 900 x 900mm (1 piece) leaf and allows the passage of wheelchairs, baby carriages, etc. You can opt for a larger passage width (2 pieces) of 1800mm, which allows the entry of 3-4 people at the same time.

The post is made of stainless steel and has a diameter of 168mm, it can be installed in any narrow place. The top panel is black tempered glass and is surrounded by a LED light bar, red or green depending on the validity of the passage.

**3 years warranty.** With standard relay signal, it can be integrated with any type of third party access control system. It is ideal for areas with pedestrian traffic: buildings, public restrooms, libraries, movie theaters, gymnasiums, etc.



# CAPELLA 8000 Rotary Turnstile

The glass of the CAPELLA 8000 is one-piece and has a large surface, it can be customized with your logo.

## Features

- Anti-interruption function: The turnstile locks automatically until it receives the opening signal.
- Automatic restart function: If the user does not pass within the prescribed time, the system will cancel the current user's authority automatically.
- Fire safety requirements: when power off, the turnstile will open automatically.
- Generally, it is controlled by button or remote control; the card reader can be installed on the wall.



## Technical specifications

Frame material	stainless steel 304	
Arm material	plexiglass / stainless steel	
Dimensions	168 * 1050 mm	
Weight	60kg/pcs	
Pitch width	600-900mm (one step)	
Pitch direction	Monodirectional and bidirectional	
MCBF	5 million	
Power supply	AC220V/110V, 50/60Hz	
Operating voltage	24V DC	
Power consumption	40W	
Operating temperature	-15 °C - 60 °C	
Operating humidity	0 ~ 95% (no freezing)	
Operating environment	Indoor / Outdoor	
Flow rate	30 persons per minute	
LED indicator	Yes	
Infrared sensor	Optional	
Communication	Communication Dry contact, relay signal, RS485	

## Dimensions (mm)

Pitch/arm width: ≤900mm or 900-1800mm

