

## KÖBER

## PRODUCT INFORMATION

Information requirements for boiler space heaters, boiler combination heaters and cogeneration space heaters (COMMISSION DELEGATED REGULATIONS No. 811-814/2013)

Model(s): C38GC25v1, CONDENS PLUS 100 25								
Condensing boiler [yes/no]:			yes	S				
Low-temperature (**) boiler [yes/no]: yes								
B1 boiler [yes/no]: no								
Cogeneration space heater [yes/no]: no					If yes, equipped with a supplementary heater: [yes/no]: no			
Combination heater [yes/no]: yes								
Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated heat output	Prated	26	kW		Seasonal space heating energy efficiency	$\eta_{\mathcal{S}}$	91	%
For boiler space heaters and boiler combination heaters: Useful heat output					For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	P <sub>4</sub>	26,0	kW		At rated heat output and high-temperature regime (*)	η4	87	%
At 30 % of rated heat output and low-temperature regime (**)	P <sub>1</sub>	5	kW		At 30 % of rated heat output and low-temperature regime (**)	η <sub>1</sub>	95	%
Auxiliary electricity consumption					Other items			_
At full load	elmax	0,085	kW	:	Standby heat loss	P <sub>stby</sub>	0,4	kW
At part load	elmin	0,075	kW		Ignition burner power consumption	Pign	0,0	kW
In standby mode	$P_{SB}$	0,003	kW		Emissions of nitrogen oxides	NOx	14	mg/kWh
				-	Noise level	Lwa	48	dB
For combination heaters:								
Declared load profile		XL			Water heating energy efficiency	η <sub>wh</sub>	84,2	%
Daily electricity consumption	Q <sub>elec</sub>	0,10	73 kWh		Daily fuel consumption	Q <sub>fuel</sub>	19,83	kWh
Annual electricity consumption	AEC	39,1	16 kWh		Annual fuel consumption	AFC	15,62	GJ
Contact details: office.vaduri@ www.motan.ro Telephone: 0233 241746 Fax: 0233 241929		town,	Neamt Disct	rict, R				eamt
(*) High-temperature regime (**) Low temperature means temperature (at heater inlet)	for conder	°C return t nsing boiler	emperature ars 30 °C, for l	at hea ow-te	ater inlet and 80 °C feed temp mperature boilers 37 °C and	perature at hea for other heate	ter outlet. ers 50 °C re	eturn

Seasonal space heating energy efficiency class: Water heating energy efficiency class:

A

KOBER Ltd Vaduri Branch, 01.11.2020

Branch Manager eng. Theodor Farcas

STR. ZORELELOR NR. 25, SAT VADURI, COMUNA ALEXANDRU CEL BUN, JUDETUL NEAMT, ROMANIA, COD POSTAL 617511 C.I.F. RO2005144 BCR: RO53 RNCB 0196 0277 8883 0005 BTRL:RO79 BTRL 0280 1202 3631 46XX

KÖBER SRL DUMBRAVA ROSIE SUCURSALA VADURI <u>TEL</u>: 0040-233-241746 0040-233-241933 <u>FAX</u>: 0040-233-241929

E-mail : office.vaduri@kober.ro
Url : www.motan.ro