

KÖBER

PRODUCT INFORMATION

Information requirements for boiler space heaters, boiler combination heaters and cogeneration space heaters (COMMISSION DELEGATED REGULATIONS No. 811-814/2013)

Model(s):				C3	8 G	C35v1, CONDENS PL	.US 100 35	5		
Condensing boiler [yes/no]: yes					,					
Low-temperature (**) boiler [yes/no]: yes										
B1 boiler [yes/no]: no										
Cogeneration space heater [yes/no]: no					If yes, equipped with a supplementary heater: [yes/no]: no					
Combination heater [yes	s/no]: yes									
Item	Symbol	Value		Unit		Item	Symbol	Value	Unit	
Rated heat output	Prated	35		kW		Seasonal space heating energy efficiency	$\eta_{\mathcal{S}}$	91	%	
For boiler space heaters and boiler combination heaters: Useful heat output						For boiler space heaters and boiler combination heaters: Useful efficiency				
At rated heat output and high-temperature regime (*)	P ₄	35,0		kW		At rated heat output and high-temperature regime (*)	η4	87	%	
At 30 % of rated heat output and low-temperature regime (**)	P ₁	6		kW		At 30 % of rated heat output and low-temperature regime (**)	η ₁	95	%	
Auxiliary electricity consumption						Other items			_	
At full load	elmax	0,088		kW		Standby heat loss	P _{stby}	0,4	kW	
At part load	elmin	0,076		kW		Ignition burner power consumption	P _{ign}	0,0	kW	
In standby mode	P_{SB}	0,004		kW		Emissions of nitrogen oxides	NOx	14	mg/kWh	
			- 1		'	Noise level	LWA	48	dB	
For combination heaters:										
Declared load profile		XL				Water heating energy efficiency	ηwh	85,47	%	
Daily electricity consumption	Q _{elec}	0,12	0,1251			Daily fuel consumption	Q _{fuel}	19,33	kWh	
Annual electricity consumption	AEC	45,	45,66			Annual fuel consumption	AFC	15,18	GJ	
Telephone: 0233 241746 town, Neamt Disctric Fax: 0233 241929					ict,					
(*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet. (**) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).										

Seasonal space heating energy efficiency class: Water heating energy efficiency class:

A

KOBER Ltd Vaduri Branch, 01.11.2020

Branch Manager eng. Theodor Farcas

STR. ZORELELOR NR. 25, SAT VADURI, COMUNA ALEXANDRU CEL BUN, JUDETUL NEAMT, ROMANIA, COD POSTAL 617511 C.I.F. RO2005144 BCR: RO53 RNCB 0196 0277 8883 0005 BTRL:RO79 BTRL 0280 1202 3631 46XX

KÖBER SRL DUMBRAVA ROSIE SUCURSALA VADURI <u>TEL</u>: 0040-233-241746 0040-233-241933 <u>FAX</u>: 0040-233-241929

E-mail : office.vaduri@kober.ro
Url : www.motan.ro