

CE-B60 & CE-B120

Features:

- Galvanised Powder Coated
- 60L & 120L Versions
- 50mm High Efficiency Foam Insulation
- Includes Floor Standing / Wall Hung Mounting Options
- Reduces Heat Pump Cycling & Ensures Correct Flow Rates
- Can be used as a standalone electric boiler
- Standard 2 1/4" Heating Element Connection
- 1/2 PRV Connection
- Sensor Pockets
- Schematic drawings and advise available.
- Internal Expansion, negates the need for an external expension vessel subject to piping arangement.
- (Reduces internal capacity to 45L & 100L)



CE-B60

Specifications:

Model	CE-B60
Material (Inside and Outside Tank)	SS304
External Dimension	Ф470*656mm
Volume Internal	60L
Insulation Thickness	50mm
With Wall Mounting Bracket	Yes
Max Working Pressure	3 Bar
Package Size	560*560*730mm
Weight	17kg

Model	CE-B120
Material (Inside and Outside Tank)	SS304
External Dimension	Ф520*965mm
Volume Internal	120L
Insulation Thickness	40mm
With Wall Mounting Bracket	Yes
Max Working Pressure	3 Bar
Package Size	630*630*1000mm
Weight	30.7kg



CE-B120

Specifications subject to change without warning.



















