

FDL

7X7 FLOODLIGHT (Selectable CCT3)

PROJECT: SCHEDULE: DATE: PREPARE BY: NOTES:

DESCRIPTION

naturaLED® 7X7 selectable wattages and selectable color temperature floodlight provide a range to fit your needs. Our floodlights has a flood beam distributions and replaces up to 400 watt and photocell included. This product is water resistant rated at IP65. Creating bright, security and spot lighting for a variety of applications such as perimeter, entryway, facades, landscapes, retail and residential complexes and architectural lighting. Pre-installed 1/2" knuckle mount design can be adjustable to the angle that best suit your needs.

APPLICATIONS

Security, Architectural, Perimeter, Entryway, Pathway, Landscape







Rated Life 50,000 Hours Warranty 5 Years



FEATURES

- DLC Standard
- IP65 Rated
- UL Listed
- Selectable Wattages
- ColorTemp: Selectable (3000/4000/5000K)
- Voltage: 120-277V
 Powerfactor >0.9
 Surge Protection: 4KV
 Beam Angle: NEMA 7X7
- Dimmable: 0-10V
- CRI: >70
- Operating temperature: 40°F 113°F
- Built-in photocell sensor (turn on and off)
- Pre-installed 1/2" Knuckle Mount
- 16-inch SO Cord for easy installation
- Recommended Mounting Height: 10-25 feet
- Material: Aluminum Die-Cast and PC Lens
- Color: Black5 Year Warranty



CCT Selectable
Built-in Photocell Sensor

SAMPLE NUMBER FXFDL15SW/77/CCT3/BK-KNC

FAMILY	SERIES	WATTAGE	BEAM ANGLE	COLOR TEMP	COLOR	COLOR
FX	FDL	15SW	77	ССТЗ	BK	YK
Fixture	Floodlight	15 Selectable Wattages	7X7 NEMA	Selectable Color Temp 3000/4000/5000K	Black	Knuckle Mount


















7X7 FLOODLIGHT FLOODLIGHT & AREA LUMINAIRES


ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Mount	IP65 Rated	DLC (S/P)
9	9734	FXFDL15SW/77/CCT3/BK-KNC	3CCT	1,260	100W	1/2"	•	S
12			(30/40/50K)	1,680		Knuckle		
15			3CCT	2,100				
40	9735	FXFDL60SW/77/CCT3/BK-KNC	(30/40/50K)	5,600	250-400W	1/2"	•	S
50			3CCT	7,000		Knuckle		
60			(30/40/50K)	8,400				


15SW-Knuckle Mount Weight: 1.25-lbs






60SW-Knuckle Mount


Weight: 2.12-lbs





PACKAGE

Case Oty for 15SW 20 pc



Case Oty for 60SW 10 pc

