

CD6260C/2000mm PRECISE LATHE MACHINE

PRODUCT FEATURES

- *THE SURFACE OF THE BEDWAYS IS SUPERSONIC FREQUENCY HARDENED.
- *GEARS PRECISELY GROUND TO REDUCE NOISE.
- *SPINDLE BORE 80MM.
- *NO NEED FOR CHANGE GEAR.THE MACHINE CAN TRUN 66 KINDS OF METRIC, INCH, MODULE AND D.P. THREADS.

TECHNICAL PARAMETERS

	Model	LCD6260/2000MM
CAPACITY	Max.swing over bed	600mm
	Max.swing over cross slide	360mm
	Max.swing over gap	730mm
	Effective length of gap	260mm
	Center Distance	2000mm
	Bed Width	330mm
HEADSTOCK	Spindle hole	80mm
	Spindle nose	ISO-D8
	Spindle taper	Metric 85mm
	Spindle speed(Number)	(15steps)24-1600rpm
FEEDS AND THREADS	Max.travel of top slide	130mm
	Max.travel of cross slide	300mm
	Max.size of toolshank	25*25m ²
	Longitudinal feeds range	66kinds 0.072-4.038mm/rev
	Cross feeds range	66kinds 0.036-2.019mm/rev
	Metric threads range	66kinds 0.5-28mm
	Inch threads range	66kinds 1-56inch
	Moudle threads range	33kinds 0.5-3.5mπ
	Diametral threads range	33kinds 8-56D.P

TAILSTOCK	Dia.of tailstock sleeve	65mm
	Taper of tailstock sleeve	MT5
	Max.travel of tailstock	150mm
MOTOR	Main drive motor	7.5KW
	Rapid traverse motor	250W
	Coolant pump motor	90W
PACKING	L*W*H	343*113*180cm
WEIGHT	N.W/G.W	2250/2600kgs