

NETMAK THICKNESSING MACHINES

		KA 400	KA 500	KA 600	KA 630
Table Size	mm	420x790	520x890	620x990	640x990
Max. Working Width	mm	400	500	600	630
Max. Working Height	mm	250	250	250	250
Min. Working Height	mm	3	3	3	3
Max. Cutting Depth	mm	8	8	8	8
Number of Blades	adet/pcs	4	4	4	4
Cutter Spindle Diameter	Ø mm	110	110	120	120
Spindle RPM	d/dak RPM	4500	4500	4500	4500
Feeding Speed	m/dak m/min	7-14	7-14	7-14	7-14
Spindle Motor Power	HP/KW	5.5 /4	7.5/5.5	10/7.5	10/7.5
Feeder Motor Power	HP KW	0.8/1.22 0.6/0.9	0.8/1.22 0.6/0.9	0.8/1.22 0.6/0.9	0.8/1.22 0.6/0.9
★Table Adjustment Motor	KW	0,25	0,25	0,37	0,37
Overall Dimensions	mm	800x1000x1050	900x1100x1050	1000x1150x1050	1000x1200x1050
★★Net Weight	kg	640	740	850	860

★ This feature is not available in the manual table models of KA 400 & KA 500 .

★★ Manual table models of KA 400 and KA 500 have different weights.

- *Monoblock Steel body*
- *Door protection*
- *Electromechanical brake system*
- *Polyurethane feeders for easy feeding*
- *Sensitive adjustment possibility by means of digital table height indicator (Opt.)*
- *Long lifetime Helical Cutter Head (Opt.)*