

# GALTRI SERIES

## LED FIXED WHITE DOWNLIGHTS DIMMABLE TRI-CCT

3000K	4000K	5700K
-------	-------	-------

- Input voltage: 220-240V AC 50/60Hz
- Remote dimmable driver included
- Housing & heatsink: plastic & aluminium
- Diffuser: frosted PC
- Faceplate: PBT
- Power factor: 0.9
- Colour temperature changeable: 3000K/ 4000K/ 5700K
- GALTRI01A-02A: CCT switch on driver
- GALTRI04-05: rear switch
- LED chips: SMD2835
- CRI: ≥80
- Flex & plug: 600mm
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with sensor





### Tested & Recommended Dimmers:

BRAND	PART NO.
CLA	VELA
CLIPSAL	32E450TM, 32ELEDM
HPM	CAT400T
DIGINET	MEDM, MMDM/RT

\*Please check with Licenced electrician for Min and Max dimmer load

\*May be compatible with other untested dimmers

30,000hr Lifetime	120° Beam Angle	<b>IP44</b> Rated	DIMMABLE	<b>3YEAR</b> Replacement Warranty
-------------------	-----------------	-------------------	----------	-----------------------------------



PART NO.	LUMENS			WATT	CRI	POWER FACTOR	DIMENSIONS	CUT OUT	WEIGHT	BOX	CARTON QTY
	3000K	4000K	5700K								
<b>GALTRI01A</b>	750lm	850lm	750lm	10W	≥80	0.9	Ø113x40mm	Ø90mm	0.30kg	11.8x11.8x7.8cm	1/40
<b>GALTRI02A</b>	900lm	1020lm	900lm	12W	≥80	0.9	Ø113x40mm	Ø90mm	0.30kg	11.8x11.8x7.8cm	1/40
<b>GALTRI04</b>	1700lm	2000lm	1800lm	20W	≥80	0.9	Ø174x41.6mm	Ø150mm	0.57kg	17.8x17.8x7.2cm	1/24
<b>GALTRI05</b>	2250lm	2600lm	2350lm	25W	≥80	0.9	Ø220x41.7mm	Ø200mm	0.63kg	22.3x22.3x7.2cm	1/16

\*Must be installed by a licenced electrician (Installation instructions sheet provided in each product box)