



BWA Reinforcement continuity system

- Double row / standard type stirrup form = type "B" / length of element 125 cm

| article no. | designation | steel "ds" Ø mm | stirrup | | | "lü" mm | box | | | pallet m |
|----------------|---------------|-----------------------|-----------------------|---------------------|-------------------------|------------|--------------------|----------------------|------------------------------|-------------|
| | | | distance "s" in mm | height "h" in mm | dimensions "v" in mm | | width "B" in mm | height "H1" in mm | height "H2" with cover mm | |
| BWA 190 | | | | | | | | | | |
| 1900815 | BWA 190-08/15 | 8 | 150 | 170 | 152 | 320 | 186 | 12 | 24 | 125 |
| 1900820 | BWA 190-08/20 | 8 | 200 | 170 | 152 | 320 | 186 | 12 | 24 | 125 |
| 1900825 | BWA 190-08/25 | 8 | 250 | 170 | 152 | 320 | 186 | 12 | 24 | 125 |
| BWA 190 | | | | | | | | | | |
| 1901010 | BWA 190-10/10 | 10 | 100 | 170 | 154 | 390 | 186 | 12 | 30 | 125 |
| 1901015 | BWA 190-10/15 | 10 | 150 | 170 | 154 | 390 | 186 | 12 | 30 | 125 |
| 1901020 | BWA 190-10/20 | 10 | 200 | 170 | 154 | 390 | 186 | 12 | 30 | 125 |
| 1901025 | BWA 190-10/25 | 10 | 250 | 170 | 154 | 390 | 186 | 12 | 30 | 125 |
| BWA 190 | | | | | | | | | | |
| 1901210 | BWA 190-12/10 | 12 | 100 | 170 | 156 | 430 | 186 | 12 | 36 | 125 |
| 1901215 | BWA 190-12/15 | 12 | 150 | 170 | 156 | 460 | 186 | 12 | 36 | 125 |
| 1901220 | BWA 190-12/20 | 12 | 200 | 170 | 156 | 460 | 186 | 12 | 36 | 125 |
| 1901225 | BWA 190-12/25 | 12 | 250 | 170 | 156 | 460 | 186 | 12 | 36 | 125 |
| BWA 220 | | | | | | | | | | |
| 2200815 | BWA 220-08/15 | 8 | 150 | 170 | 188 | 320 | 222 | 12 | 24 | 80 |
| 2200820 | BWA 220-08/20 | 8 | 200 | 170 | 188 | 320 | 222 | 12 | 24 | 80 |
| 2200825 | BWA 220-08/25 | 8 | 250 | 170 | 188 | 320 | 222 | 12 | 24 | 80 |
| BWA 220 | | | | | | | | | | |
| 2201010 | BWA 220-10/10 | 10 | 100 | 170 | 190 | 390 | 222 | 12 | 30 | 80 |
| 2201015 | BWA 220-10/15 | 10 | 150 | 170 | 190 | 390 | 222 | 12 | 30 | 80 |
| 2201020 | BWA 220-10/20 | 10 | 200 | 170 | 190 | 390 | 222 | 12 | 30 | 80 |
| 2201025 | BWA 220-10/25 | 10 | 250 | 170 | 190 | 390 | 222 | 12 | 30 | 80 |
| BWA 220 | | | | | | | | | | |
| 2201210 | BWA 220-12/10 | 12 | 100 | 170 | 192 | 460 | 222 | 12 | 36 | 80 |
| 2201215 | BWA 220-12/15 | 12 | 150 | 170 | 192 | 460 | 222 | 12 | 36 | 80 |
| 2201220 | BWA 220-12/20 | 12 | 200 | 170 | 192 | 460 | 222 | 12 | 36 | 80 |
| 2201225 | BWA 220-12/25 | 12 | 250 | 170 | 192 | 460 | 222 | 12 | 36 | 80 |
| BWA 240 | | | | | | | | | | |
| 2400815 | BWA 240/08-15 | 8 | 150 | 170 | 208 | 320 | 242 | 12 | 24 | 80 |
| 2400820 | BWA 240/08-20 | 8 | 200 | 170 | 208 | 320 | 242 | 12 | 24 | 80 |
| 2400825 | BWA 240/08-25 | 8 | 250 | 170 | 208 | 320 | 242 | 12 | 24 | 80 |
| BWA 240 | | | | | | | | | | |
| 2401010 | BWA 240/10-10 | 10 | 100 | 170 | 210 | 390 | 242 | 12 | 30 | 80 |
| 2401015 | BWA 240/10-15 | 10 | 150 | 170 | 210 | 390 | 242 | 12 | 30 | 80 |
| 2401020 | BWA 240/10-20 | 10 | 200 | 170 | 210 | 390 | 242 | 12 | 30 | 80 |
| 2401025 | BWA 240/10-25 | 10 | 250 | 170 | 210 | 390 | 242 | 12 | 30 | 80 |
| BWA 240 | | | | | | | | | | |
| 2401210 | BWA 240/12-10 | 12 | 100 | 170 | 212 | 460 | 242 | 12 | 36 | 80 |
| 2401215 | BWA 240/12-15 | 12 | 150 | 170 | 212 | 460 | 242 | 12 | 36 | 80 |
| 2401220 | BWA 240/12-20 | 12 | 200 | 170 | 212 | 460 | 242 | 12 | 36 | 80 |
| 2401225 | BWA 240/12-25 | 12 | 250 | 170 | 212 | 460 | 242 | 12 | 36 | 80 |