

# **TECHNICAL DATA SHEET**

n° DTE 14-065\_EN cancels and replaces N° DTE 13-001\_EN

# **SOPRADERE**

**SOPRADERE** is a ready-to-use cold applied bitumen primer composed of bitumen, volatile solvents and adhesive additives.

In accordance with French Code of Practice DTU 43 (NF P 84-204).

# **User application**

**SOPRADERE** is used as cold-applied primer to increase adhesion for bitumen-based waterproofing membranes. It is also used as bituminous coating for buried walls and foundations.


All the applications are described in Technical Approval or **SOPREMA**'s Technical Guidelines in force.


# Composition

	SOPRADERE
Physical state	Black homogeneous liquid, leaving a slightly sticky black film once dry
Dry content	> 40 % of weight
Density at 20°C	about 950 kg/m³ (± 50)
Viscosity cup n°4 at 20°C (NF T 30-014)	40 to 60 sec
Flash point (ASTM D 56)	+ 24°C
Drying time on concrete	Less than 1 hour

# Packaging .

	SOPRADERE
Packaging	Cans of 5 or 30 liters
Consumption	Consumption depends on the uses and the substrate.  On rough and absorbent substrate (i.e concrete, wood):  - 5 L can cover about 20 m <sup>2</sup> - 30 L can cover about 120 m <sup>2</sup> On smooth, non absorbent substrate (i.e metal), the average consumption may be lower.
Storage	The product can be stored until 12 months at a temperature above 0°C and protected from the sun.







# TECHNICAL DATA SHEET

n° DTE 14-065 EN cancels and replaces N° DTE 13-001 EN

#### Installation

Before use, well homogenize **SOPRADERE**. The tools used (roll, brush, rubber squeegee) must be clean.

**SOPRADERE** must be applied with a brush or a roller onto dry, clean surfaces, free of all dust and non-adhesive parts (concrete, wood, metal ... previously degreased). Let dry completely before apply the waterproofing membrane.

#### **Cleaning tools:**

Petroleum solvent (white spirit, xylene for example).

### **Special indications**

#### **Hygiene, health and environment:**

- Flammable: keep away from flames and sparks during use.
- **SOPRADERE** contains xylene.
- Ensure that all cans, empty or full, containing flammable substances are kept at least 10 m away.
- If spray gun is used, ensure that no incompatible material is used that may create sparks.
- Close cans properly after each use.
- Do not breathe in fumes.
- Avoid the product coming in contact with eyes.
- Do not smoke while product is being used.
- Do not swallow.
- Do not throw wastes into sewers.

For further information, please refer to relevant Safety Data Sheet.

#### **Quality control:**

**SOPREMA** has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.

