

DOUBLE SPLICE TAPE

Splicetronics Solutions

Part (roal)	Dimensions (pc)	Doolzaga
Part (reel)	Dimensions (pc)	Package
DPJL08 (8mm)	48mm x 3/3.5/4mm	250pcs/box
DPJL12 (12mm)	48mm x 3/2/7/2mm	250pcs/box
DPJL16 (16mm)	48mm x 3/2/11/2mm	250pcs/box
DPJL24 (24mm)	48mm x 3/2/19/2mm	250pcs/box



APPLICATION

- So Double strips of black PET tape with plastic jig pins piece
- S Possible to use without the splice tool and clip
- § 32mm-44mm available upon request

ADVANTAGES

- S Necessary for Panasonic machines with an intelligent feeder
- S The black strip allows the sensor to detect the splice
- § Jig pins included for easy alignment

INSTRUCTIONS

- (3) Use the cutting tool to accurately cut the carrier tapes.
- (S) Hold the splice tape (face down/Arrow>).
- (§) Remove the release liner to reveal the adhesive side.
- ③ Place the cut carrier tapes (cover tape down) on the alignment jig pins.
- S Remove the black alignment jig pins piece.
- § Fold over the strips to the underside of the carrier tape and press firmly.
- (§) Remove and discard the clear plastic cover to complete the splice.





