

MINI SKID STEER

V20 MINI SKID SNOW / LIGHT MATERIAL BUCKET

Available widths
36", 42", 48", 54" & 60"

High volume design for hauling
snow, mulch, and light materials.



AVAILABLE
EDGE OPTION:
STANDARD
BOLT-ON

34.7" DEPTH	23.3" HEIGHT	< 1650 LB LOADER OPERATING CAP.
----------------	-----------------	---------------------------------------

1. 3/16" SHELL & SIDE PLATES
2. 1/2" x 4" WELD-ON EDGE
3. WINDOWS FOR BETTER VISIBILITY.
AVAILABLE WITH A SOLID BACK
4. UP TO 14 CU FT STRUCK CAPACITY
(VARIES BY MODEL)
5. UP TO 17 CU FT HEAPED CAPACITY
(VARIES BY MODEL)

CHOOSE FROM THREE
MINI SKID MOUNTS:
· MINI UNIVERSAL
(All brands except
Bobcat® and ASV®)
· BOBCAT® Mini
· ASV® Mini
NOTE: None of the above
are compatible with
universal skid steer mount.

MODEL	CLMB36	CLMB42	CLMB48	CLMB54	CLMB60
Width: Overall / Inside (in.)	36.0 / 34.6	42.0 / 40.6	48.0 / 46.6	54.0 / 52.6	60.0 / 58.6
Overall Height (in.)	23.3				
Depth: Overall / Inside (in.)	34.7 / 31.3				
Capacity: Struck / Heaped (cu. ft.)	8.3 / 9.9	9.8 / 11.7	11.3 / 13.5	12.8 / 15.3	14.3 / 17.1
Bucket Back Angle (degrees)	70				
Shell Thickness (in.)	0.19				
Side Plate Thickness (in.)	0.19				
Approximate Weight (lbs)	215 ¹	235 ¹	255 ^{1,2}	275 ^{1,2}	295 ^{1,2}
Recommended Loader Capacity	Less than 1650 lbs				

¹Bobcat® mount adds 10 lbs to model weight, and ²ASV® mount adds approximately 5 lbs.

V20 MINI SKID STEER SKELETON ROCK BUCKET

Available widths 36", 42" & 48"
Pick up rocks and leave dirt behind.



0.25" GRADE 50 STEEL TINES	2.9" TINE SPACING	31.2" DEPTH	20.4" HEIGHT	> 500 LB LOADER OPERATING CAP.
-------------------------------	-------------------------	----------------	-----------------	--------------------------------------

1. EVERY TINE IS MADE FROM ONE PIECE
OF STEEL FOR MAXIMUM RIGIDITY
2. NOTCH NEAR TINE TIPS HOLDS
ROCKS SECURELY
3. TINE TIPS FULLY GUSSETED FOR
ADDED STRENGTH

CHOOSE FROM THREE
MINI SKID MOUNTS:
· MINI UNIVERSAL
(All brands except
Bobcat® and ASV®)
· BOBCAT® Mini
· ASV® Mini
NOTE: None of the above
are compatible with
universal skid steer mount.

MODEL	CSRB36	CSRB42	CSRB48
Width: Overall / Inside (in.)	36.0 / 35.0	40.9 / 39.9	46.8 / 45.8
Overall Height (in.)	20.4		
Depth: Overall / Inside (in.)	31.2 / 20.5		
Number of Tines (w/ sides)	13	15	17
Space Between Tines (in.)	2.9		
Tine Thickness (in.)	0.25 ¹		
Side Plate Thickness (in.)	0.25 ¹		
Approximate Weight (lbs)	180 ²	205 ²	225 ^{2,3}
Recommended Loader Capacity	Greater than 500 lbs		

¹Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).

²Bobcat® mount adds 15 lbs to model weight, and ASV® mount adds approximately 30 lbs.