



Schematic diagram: ProfiSkim 100 in use



Extras

Top 3 product characteristics

- Powerful suction cleaning of pond surfaces up to 80 m²
- Can be used with large filter systems and shallow water zones
- Perfect dimensions for large quantities of water

Recommendation

Ensure that the skimmer is installed in a horizontal position and confirm this with a spirit level. Place the skimmer in such a manner that you can execute maintenance tasks, such as emptying the basket.

PROFISKIM

The pro for the shallow water zone

- Powerful suction cleaning of pond surfaces up to 65 m² or up to 80 m²
- Ideal implementation in shallow water zones
- Can be used in gravity fed operation (DN 110) or pump fed operation (incl. 2" adapter)
- Water routing for effective suction capacity
- Perfect supplement for filter systems in the gravity fed, as well as the pump fed system
- Large, easy to clean stainless steel basket with 8 mm mesh width. On request, a debris basket with 2 mm mesh width is available for the ProfiSkim Premium.
- ProfiSkim Premium with stable stainless steel base for even easier installation

TECHNICAL DATA

Matching filter pumps starting on page 70



		ProfiSkim 100	ProfiSkim Premium
Dimensions (L x W)	mm	780 x 585	500 x 340
Net weight	kg	13.06	9.10
Guarantee (+ request guarantee)*P.251	Years	3 + 2	
Height adaptation		350 mm – 550 mm	
Connections, outlet	mm	50, 110	
Connections, outlet		2", DN 110	2", DN 110
Rec. flow rate (pump-fed)	l/h	10000 – 20000	6000 – 16000
Rec. flow rate (gravity-fed)	l/h	10000 – 12000	6000 – 12000
Filter volume	l	12.0	7.0
Pond surface, max.	m ²	80	65
Item no.		57134	51185

*P. 251

