

Mounting instructions Cockpit tent XL

Before you start

In your package there are mounting templates in thin white paper, which is packed together with the canvas. On the templates, there are abbreviations for different fittings you might need depending on your boat model. Below are pictures showing the fittings and the ones you need for your specific canopy is packed in a plastic bag together with the frames.

Tools you need

- 3,5 mm drill
- Counterbore
- Star-Screwdriver
- Pointy marker pen
- Sikaflex

- Put the templates on deck in line with the deck layout an other details drawn on the templates.
 Attach them with tape if needed.
- Use the pen to mark where holes for the fittings should be. **OBS!** Sometimes there are markings for both sprayhood and tent in the same template. Please see next page for definitions.
- Flip the template up-side-down and do the same thing on starboard/port side of the boat.
- Drill most of the holes. Tip: the front fittings of the tent can be drilled and attached when the tent is mounted for better fit.
- Counterbore **all** holes. Please note that **this is very important** to make sure that the gelcoat stays solid when tightening the screw.
- Put sikaflex in **all** holes.
- 7 Attach the fittings on deck. Observe the difference between Lång Norsk Knapp ("L") och Plastknapp ("PK").



Kantyxegatan 25L, 213 76 Malmö Tel: +46 (0)40 15 40 17 www.kapell-annat.se info@kapell-annat.se



- Mount the frames in its fittings. Observe how the frames should be standing before tightening the screws. Use someones help to hold the frames, make this a lot easier.
- Take the canvas and do the following:
 - Mount the roof and attach the front part to the sprayhood.
 - Tighten the canvas backwards using the straps. Make sure the straps are attached to the frame in the pre-cut holes in the frame tunnel of the canvas (see picture previous side). Observe that tents with support poles does not have straps.
 - If your frame has supportpoles, detach them to help the canvas find its right position.
- Attach the sides and rear pieces. Tighten eventual straps on the inside and readjust support poles position when canvas is properly mounted.



Please find instruction videos for mounting on our youtubechannel. Follow this <u>link</u>

Definitions templates

Explanation fitting types

DB Rakt däcksbeslag
DBV Vinklat däcksbeslag
DB XL Däcksbeslag XL
RB or R Rutgersson beslag

PK Plastknapp

KR or GF Plastkrok, gripfix L or LK Lång norsk knapp

TK Tryckknapp NB Nyckelbeslag

M Minax

Explanation other

SH or SP Sprayhood
T Cockpit tent
XLT XL cockpit tent

BB Port

SB Starboard



KAPELL & ANNAT

Kantyxegatan 25L, 213 76 Malmö Tel: +46 (0)40 15 40 17 www.kapell-annat.se info@kapell-annat.se