MPW501

Replaces date: 3/8/2021

Revision date: 1/24/2022 Version: 1.2.0

SECTION 1: Identification

1.1. GHS Product identifier

Trade name:

MPW501

Article no

Article no	Description
003481000005	

1.2. Recomended use of the chemical and restrictions on use

Recommended uses: Lubricant.

1.3. Supplier's details

Supplier	
Company:	Mouldpro ApS
Address:	Baltorpbakken 10
Zip code:	2750
City:	Ballerup
Country:	DENMARK
E-mail:	sales@mouldpro.com
Phone:	+45 70 20 31 31
Homepage:	www.mouldpro.com

1.4. Emergency phone Number

Pictograms

+ 45 70 20 31 31 (Mouldpro) The emergency telephone is open between 8 a.m. and 4 p.m. on workdays.

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification:	Aerosols, Category 1;H222 Aerosols, Category 1;H229 Skin irritation, Category 2;H315 Specific target organ toxicity - single exposure, Category 3;H336 Reproductive toxicity, Category 2;H361f Hazardous to the aquatic environment, short-term (Acute), Category 3;H402 Hazardous to the aquatic environment, long-term (Chronic), Category 2;H411
Most serious harmful effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Harmful to aquatic life. Toxic to aquatic life with long lasting effects. Prolonged or repeated inhalation of vapors may cause damage to the central nervous system. The product releases organic solvent vapors which may cause drowsiness and dizziness. At high concentrations, the vapors may cause headache and intoxication.

2.2. GHS label elements, including precautionary statements



MPW501

Replaces date: 3/8/2021

Revision date: 1/24/2022 Version: 1.2.0

Substance:	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics;	
Hazard Statements		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H361f	Suspected of damaging fertility.	
H402	Harmful to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
Precautionary statements		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P261	Avoid breathing vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P410+412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.	

2.3. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No./ EC No./ REACH Reg. No.	Concentration	Notes
Petroleum gases, liquefied (with <0,1% 1,3-Butadiene)	68476-85-7 270-704-2	30 -< 60 %	
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35	10 -< 30 %	3
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9 919-857-5	5 -< 10 %	3
n-hexane	110-54-3 203-777-6	< 1 %	3
2-(2-heptadec-8-enyl-2- imidazolin-1-yl)ethanol	95-38-5 202-414-9 01-2119777867-13	< 1 %	17

3 = H304 is not applicable due to use as aerosols.

17 = M (acute) = 10

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures		
Inhalation:	Seek fresh air. Seek medical advice in case of persistent discomfort.	
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.	
Skin contact:	Remove contaminated clothing. Seek medical advice in case of persistent discomfort. Wash skin with soap and water.	
Eye contact:	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek	

MPW501

Replaces date: 3/8/2021

Revision date: 1/24/2022 Version: 1.2.0

	medical advice if symptoms persist.		
Burns:	Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.		
General:	Bring the safety data sheet or label when seeking medical advice.		

4.2. Most important symptoms/effects, acute and delayed

If ingested, can be irritating to mucous membranes of the mouth and gastrointestinal tract. Irritating to skin - may cause reddening. The product releases organic solvent vapors which may cause drowsiness and dizziness. At high concentrations, the vapors may cause headache and intoxication. Inhalation of spray mist may cause chemical pneumonia. Prolonged or repeated inhalation of vapors may cause damage to the central nervous system. Suspected of damaging fertility.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No special immediate treatment required.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

 Suitable extinguishing media:
 Extinguish with powder, foam or water mist. Use water or water mist to cool non-ignited stock.

 Unsuitable extinguishing media:
 Do not use a jet of water, as it may spread the fire.

5.2. Specific hazards arising from the chemical

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released. Heating will cause a rise in pressure in packaging with a risk of bursting. CAUTION! Aerosol containers may explode.

5.3. Special protective actions for fire-fighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapor and smoke gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stay upwind/keep distance from source. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment. Provide adequate ventilation. Smoking and naked flames prohibited. Wear safety goggles if there is a risk of eye splash. Wear gloves. Wear respiratory protective equipment.

For emergency responders: In addition to the above: Protective suit is recommended.

6.2. Environmental precautions

Avoid unnecessary release to the environment.

6.3. Methods and materials for containment and cleaning up

Wipe up drops and splashes with a cloth.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Copyright © 1995 - 2022 DGOffice B.V., www.DGOffice.net

MPW501

Replaces date: 3/8/2021

Revision date: 1/24/2022 Version: 1.2.0

Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment. Smoking and naked flames prohibited. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk during pregnancy.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, drugs, etc. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Store in a dry, cool, well-ventilated area. Avoid direct sunlight.

7.3. Specific end use(s)

No special uses in addition to identified uses in 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

•••••••••••••••••••••••••••••••••••••••		
Occupational exposure limit:	t: There are no official GHS occupational exposure limits. Be aware of possible national occupational exposure limits.	
Measuring methods:	Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.	
8.2. Exposure controls		
Appropriate engineering controls:	Wear the personal protective equipment specified below.	
Personal protective equipment, eye/face protection:	nt, Wear safety goggles if there is a risk of eye splash.	
Personal protective equipment, hand protection:	Wear gloves. Type of material: Butyl rubber. Breakthrough time has not been determined for the product. Change gloves often. The suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, glove material thickness, functionality and chemical resistance. Always seek advice from the glove supplier.	
Personal protective equipment, respiratory protection:	Light use (small volume, shortterm contact (below 10 min.)): Not required. Medium use (medium volume, medium contact (1-2 hours)): Wear respiratory protective equipment. Filter type: A.	
Environmental exposure controls:	Ensure compliance with local regulations for emissions.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter		Value/unit
Physical state	Aerosol	
Color	No data	
Odour	Solvent	
Solubility	No data	
Parameter	Value/unit	Remarks
Odour threshold	No data	
Melting point	No data	
Freezing point	No data	
Boiling point or initial boiling point and boiling range	-402 °C	(LPG)
Flammability	No data	

Safety Data Sheet		
MPW501		
Replaces date: 3/8/2021		Revision date: 1/24/2022 Version: 1.2.0
Lower and upper flammability limit	No data	

Lower and upper explosion limit	1.4 - 10.9 vol%	(LPG)
Flash Point	-104 °C	(LPG)
Auto-ignition temperature	365 °C	(LPG)
Decomposition temperature	No data	
pH (solution for use)	No data	
pH (concentrate)	No data	
Kinematic viscosity	No data	
Viscosity	No data	
Partition coefficient n-octanol/water (log value)	No data	
Vapour pressure	590 - 1760 kPa	(LPG)
Density	No data	
Relative density	No data	
Relative vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

9.2. Other information

Other Information: None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts under heat generation with the following: Oxidisers. The product may ignite on contact with e.g. heat or a spark.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

Product vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources. Avoid direct sunlight. Avoid temperatures >50°C.

10.5. Incompatible materials

Oxidisers.

10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

SECTION 11: Toxicological information

11.1. Information on health hazard classes

Acute toxicity - oral:	The product does not have to be classified. Test data are not available. Spray mist in mouth may irritate mucous membranes in mouth and throat.	
Acute toxicity - dermal:	The product does not have to be classified. Test data are not available.	
Acute toxicity - inhalation:	The product does not have to be classified. Test data are not available.	
Skin corrosion/irritation:	Irritating to skin - may cause reddening.	
Copyright © 1995 - 2022 DGOffice B.V., www.DGOffice.net		

MPW501

Replaces date: 3/8/2021

Revision date: 1/24/2022 Version: 1.2.0

Serious eye damage/eye irritation:	The product does not have to be classified. Test data are not available. May cause eye irritation.				
Respiratory sensitization or skin sensitization:	The product does not have to be classified. Test data are not available.				
Germ cell mutagenicity:	The product does not have to be classified. Test data are not available.				
Carcinogenic properties:	The product does not have to be classified. Test data are not available.				
Reproductive toxicity:	Suspected of damaging fertility.				
Single STOT exposure:	If ingested, can be irritating to mucous membranes of the mouth and gastrointestinal tract. The product releases organic solvent vapors which may cause drowsiness and dizziness. At high concentrations, the vapors may cause headache and intoxication.				
Repeated STOT exposure:	The product does not have to be classified. Test data are not available. Prolonged or repeated inhalation of vapors may cause damage to the central nervous system.				
Aspiration hazard:	The product does not have to be classified. Test data are not available. Inhalation of spray mist may cause chemical pneumonia.				
11.2. Information on other hazards					
Endocrine disrupting properties:	None known.				
Other toxicological effects:	None known.				

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Test data are not available.

12.3. Bioaccumulative potential

Test data are not available. No bioaccumulation expected.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

None known.

12.7. Other adverse effects

Volatile organic compound (VOC). Potential for photo-chemical formation of ozone.

SECTION 13: Disposal considerations

MPW501

Revision date: 1/24/2022 Version: 1.2.0

13.1. Disposal methods

Avoid unnecessary release to the environment. Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility.

SECTION 14: Transport information

Land transport (ADR/RID)			
14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS	14.5. Environmental hazards:	The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es):	2.1		-
Hazard label(s):	2.1		
Hazard identification number:		Tunnel restriction code:	D
Inland water ways transport	t (ADN)		
14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS	14.5. Environmental hazards:	The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es):	2.1		-
Hazard label(s):	2.1		
Transport in tank vessels:			
Sea transport (IMDG)			
14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS	14.5. Environmental hazards:	The product must be labelled as a Marine Pollutant (MP) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es):	2.1	Environmental Hazardous Substance Name(s):	
Hazard label(s):	2.1		
EmS:	F-D, S-U	IMDG Code segregation group:	- None -
Air transport (ICAO-TI / IAT	A-DGR)		
14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE	14.5. Environmental hazards:	The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es):	2.1		
Hazard label(s):			

Copyright © 1995 - 2022 DGOffice B.V., www.DGOffice.net

MPW501

Replaces date: 3/8/2021

14.6. Special precautions for user

None.

14.7. Transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

Special Provisions: None.

15.2. Chemical Safety Assessment

Other Information:

Chemical safety assessment has not been performed.

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes		
1.2.0	1/24/2022	Bureau Veritas HSE - DOL	3,9,11,12,16		
1.1.0	3/8/2021	Bureau Veritas HSE - DOL	2-4,8-12,14-16		
Abbreviations:	PBT: Persistent, Bioaccumulative and Toxic STOT: Specific Target Organ Toxicity vPvB: Very Persistent and Very Bioaccumulative				
Other Information:	This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with GHS Rev. 7 (2017).				
Training advice:	A thorough knowledge of this safety data sheet should be a prerequisite condition.				
Classification method:	Calculation based on the hazards of the known components.				
SDS is prepared by					
Company:	Bureau Veritas HSE Denmark A/S				
Address:	Oldenborggade 25-31				
Zip code:	7000				
City:	Fredericia				
Country:	DENMARK				
E-mail:	infohse@dk.bureauveritas.com				
Phone:	+45 77 31 10 00				
Homepage:	www.bureauveritas.dk				
Country:	UN				

Revision date: 1/24/2022

Version: 1.2.0