



GENERAL INFO **TASTE, ODOUR AND CHLORINE REDUCTION**

Carbon Block Cartridges

The Puretec CB Series cartridges are highly effective in reducing, taste, odour, chlorine, and sediment. Cyst, lead, heavy metal, high turbidity and sulphur removal models are also available. The ultimate for beautiful drinking water.

The Puretec CB cartridges are constructed from bonded activated carbon, offering superior treatment of water with no release of carbon fines.

MATERIALS OF CONSTRUCTION

- Filter Media Bonded PAC
- End Caps Polypropylene
- Outer Wrap Polyolefin
- Netting Polyethylene
- Gaskets Buna-N
- Temperature Rating 40°F to 180°F
(4.4°C to 82°C)

FEATURES & BENEFITS

- Ultimate in carbon cartridges
- No carbon fines and superior contaminant capacity
- Flow rates up to 60 litres/minute
- Temperature rating up to 82°C
- High dirt holding tolerance maximizes utilization of the carbon-block
- Enhanced dirt holding capacity for extended cartridge life
- Reduces chlorine, bad taste and odour

HOUSING SPECIFICATIONS AND PERFORMANCE DATA

	Model	Dimensions	Description	Micron Rating (Nominal)	Flow (Lpm)
5"	CB955	standard 2.5" x 9"	cyst reduction*	0.5	8
10"	CB951	standard 2.5" x 10"	cyst reduction*	0.5	15
	CB951-H	standard 2.5" x 10"	cyst, heavy metal removal	0.5	15
	CB051	standard 2.5" x 10"		5	16
	CB101	standard 2.5" x 10"		10	18
20"	CB952	standard 2.5" x 20"	cyst reduction*	0.5	28
	CB052	standard 2.5" x 20"		5	30
	CB102	standard 2.5" x 20"		10	32
10"	CB95MP1	MaxiPlus™ 4.5" x 10"	cyst reduction*	0.5	20
	CB05MP1	MaxiPlus™ 4.5" x 10"		5	24
	CB10MP1	MaxiPlus™ 4.5" x 10"		10	30
20"	CB95MP2	MaxiPlus™ 4.5" x 20"	cyst reduction*	0.5	40
	CB05MP2	MaxiPlus™ 4.5" x 20"		5	48
	CB10MP2	MaxiPlus™ 4.5" x 20"		10	60

*99.9% reduction of Cryptosporidium and Giardia cysts

