

Great results for small workgroups.

The M2635dn is the most affordable model in our new ECOSYS series, yet it is still full of features. As extremely reliable devices with 1,200 dpi b/w print quality, duplex printing, gigabit Ethernet and overall fast scanning and copying, it is perfectly suited for demand-ing desktop users and small workgroups.



Specifications

ECOSYS

ECOSYS stands for ECOlogy, ECOnomy and SYStem-printing. With their longlife components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridgefree system means that toner is the only consumable. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.

Enviromental print features

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode), Quiet mode (reduced print speed).

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows© PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

USB Host Interface for USB Flash Memory
Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Application-based Profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed with activated duplex mode as standard, thus leading to a reduced paper consumption.

ECOSYS M2635dn

GENERAL

Technology: KYOCERA ECOSYS Laser Control panel display: 5 line LCD display Engine speed: Up to 35 pages A4 per minute Resolution: 300 dpi, 600 dpi, 1,200 dpi Warm-up time: Approx. 17 seconds or less Time to first print: Approx. 6.8 seconds or less Time to first copy: Approx. 6.9 seconds or less

CPU: 800 MHz Memory: Standard 512 MB, max. 1,536 MB

Standard interface:
USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet
(10BaseT/100BaseTX/1000BaseT), Slot for optional SD/
SDHC-Card

Dimensions (W \times D \times H): Main unit: 417 \times 412 \times 437 mm

Weight: Main unit: Approx. 19 kg Power source: AC 240 V, 50 Hz Power consumption: Copy/Print BW: 661 W

Ready mode: 21 W Sleep-mode: 1 W

Noise (Sound pressure level: ISO 7779/ISO 9296):

Copy/Print: 47.2 dB(A) LpA Quiet mode: 44.1 dB(A) LpA

Ready/Standby mode: Immeasurably low

Sleep mode: Immeasurably low

Safety standards: AS/NZ s3260 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray; 60 – 220 g/m2; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm –216 x 356 mm) 250-sheet universal cassette; 60 – 163 g/m2; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 – 216 x 356

mm). Max. input capacity with options: 850 sheets **Duplex functionality as standard:** Double-sided printing: 60 – 163 g/m²; A4, A5, B5, Letter, Legal

Document processor: 50-sheet, 50–160 g/m2, A4, A5, A6, B5, B6, Letter, Legal, Custom (100 x 148 to 216 x 356 mm) Output capacity: Max. 150 sheet face down with paper full

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc Emulations: PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPDL 3), PDF Direct Print, XPS/OpenXPS

Operating systems: All current Windows operating systems, MACOSXVersion 10.5 or higher, Unix, Linux aswell as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL6/KPDL3, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available

COPY FUNCTIONS

Max. original size: A4(Platen)/Legal(DP) Continuous copying: 1 - 999***

Zoom range: 25 — 400% in 1% steps

Preset magnification ratios: 7 Reductions/5 Enlargements

Exposure mode: Manual: 9 steps

Image adjustments: Text + Photo, Photo, Text, Map Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, priority print, program, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS (Simplex)

Functionality: Scan-to-e-mail (SMTP), Scan-to-FTP (FTP over SSL), Scan-to-SMBv3, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)

Scan speed: 40 ipm (300 dpi, A4, b/w), 23 ipm (300 dpi, A4, colour)

Scan resolution: 300dpi x 300dpi, 200dpi x 200dpi(Default), 200dpi x 100dpi , 600dpi x 600dpi, 400dpi x 400dpi, 200dpi x 400dpi

Max. scan size: A4(Platen), Legal(DP)

Original recognition: Text + Photo, Photo, Text, Light Text/ Fine Line, Text (for OCR)

Scan file formats: TIFF, PDF, PDF/A-1 , high compression PDF, encrypted PDF, JPEG, XPS

Compression method: MMR/JPEG

Features: Integrated address book, LDAP, encrypted data transfer, Blank sheet skip

FAX FUNCTIONS

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Less than 3 seconds Scanning speed: 2 sec/sheet or less

Address book: 200 entries

Scanning densifies: Normal: 200 x 100 dpi, Fine: 200 x 200 dpi, Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi

Maximum original size: A4, Legal

Compression method: JBIG, MMR, MR, MH

Features: Network fax, duplex transmission and reception, polling transmission and reception

CONSUMABLES

Average continuous toner yield in accordance with ISO 19752

Toner-Kit TK-1184: toner yield 3,000 pages A4 Starter toner: toner yield 1,000 pages A4

PF-1100 Paper feeder (max. 2 units): 250 sheets; 60 - 163 g/m2; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm — 216 x 356 mm)

Memory upgrade: DIMM-1GBE: 1,024 MB

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): Support

for various authentication keys available

Operation is remarkably quiet and, with even smaller dimensions than their predecessors, they fit on virtually every desk. Finally, thanks to many flexible paper-handling options, the device can be customised to meet your demands precisely.















KYOCERA Document Solutions Australia Ph: 13 59 62

www.kyoceradocumentsolutions.com.au



PO Box 1167 North Cairns 4870 Ph- 4080 2000

Fax- 4080 2020

info@evolvecairns.com.au www.evolvecairns.com.au

KYOCERA Document Solutions Partner

JUNE2021/ECOSYSM2635dn

KYOCERA Document Solutions New Zealand Ph: 0800 459 623

www.kyoceradocumentsolutions.co.nz



kyoceradocumentsolutions.com.au

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444