


The colour professional.

This A4 colour device is designed specifically for medium and large-sized work groups. This colour printing solution with big potential contains our renowned long-life components, which help to reduce waste and ensure exceptional levels of reliability.



ECOSYS P6230cdn



Compact design with full functionality

Double-sided print as standard

Low power consumption saves energy

Specifications

ECOSYS

The ECOSYS P6230cdn incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. They combine effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

GENERAL

Technology: KYOCERA ECOSYS, Laser, Colour

Operation panel: 2Line display with back light and key buttons to navigate

Type: Desktop

Engine speed: Up to 30 pages A4 per minute

Duplex print speed: 15 page per minute, A4

Resolution: 1200 x 1200 dpi (print, at reduced speed)

Warm-up time: Approx. 26 seconds or less

Time to first print: Approx. 6/7 seconds or less in b/w / colour

CPU: ARM Cortex-A9 Dual core 1.2GHz + ARM Cortex-M3 100MHz

Memory: Standard 1GB, Max. 1GB + 128GB SSD

Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/

1000BaseT, IPv6, IPv4, IPsec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 1 eKUIO slot for optional internal print server, Slot for optional SD Card

Integrated accounting: 100 department codes

Dimensions (W x D x H): 390 x 532 x 409.5 mm

Weight: Approx. 28.3 kg

Power source: AC 220 ~ 240 V, 50Hz

Power consumption

Printing: 466 W

Low power mode: -- W

Ready mode: 56 W

Sleep-mode: 0.6 W

Noise (sound pressure level: ISO 7779/ISO 9296)

Copying/Printing: 49.5 dB (A)

Stand-by: 30 dB (A)

Safety standards: AS/NZS3260

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity:

100-sheet multi-purpose tray, 60–220 g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (70 x 148 to 216 x 356 mm), 500-sheet Standard universal paper cassette, 60–163 g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm). Max. input capacity with options: 2,100 sheets A4

Duplex unit: Duplex as standard supports 60–163 g/m², A4, A5, B5, Letter, Legal

Output capacity: Max. 250 sheets face-down with paper full sensor

PRINT FUNCTIONS

Controller language: PRESCRIBE II c

Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

Operating systems: All current Windows operating systems, MAC OS X Version 10.8 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL), 93 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Wi-Fi Direct (optional), Google cloud print

CONSUMABLES

Average continuous toner yield in accordance ISO/IEC 19798

TK-5274K Toner Kit: Micro fine black for 8,000 pages A4

TK-5274C, TK-5274M, TK-5274Y Toner Kits: Micro fine toner cyan, magenta, yellow for 6,000 pages A4. Capacity of starter toner is black 3,500 pages, cyan, magenta, yellow 2,500 pages A4

OPTIONS

Paper handling

PF-5100 Paper feeder (max 3 units): 500 sheets, 60–220 g/m², A4, A5, B5, Letter, Legal, Custom (92 x 162 mm to 216 x 356 mm)

HD-6 SSD: 32 GB for easy document management

HD-7 SSD: 128 GB for easy document management

Data Security Kit (E): In line with ISO 15408

(Common Criteria) with security level EAL2

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available

Optional interface:

IB-36: WLAN and Wi-Fi Direct Interface

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1,000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

1277 Cabinet

The ECOSYS P6230cdn has five paper sources, this printer allows for different media sizes and weights, up to 220g/m². It is the ideal Colour Printer if you want to take a next professional step with your business as well as your running costs.





PO Box 1167
North Cairns 4870
Ph- 4080 2000
Fax- 4080 2020
info@evolvecairns.com.au
www.evolvecairns.com.au
KYOCERA Document Solutions Partner

JUNE2021/ECOSYS P6230cdn

KYOCERA Document Solutions Australia

Ph: 13 59 62

www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand

Ph: 0800 459 623

www.kyoceradocumentsolutions.co.nz



kyoceradocumentsolutions.com.au

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444