

Improved Quality and Reliability to help you Grow

Designed to operate in demanding high-end work environments and keep up with your ever-changing way of working. These user friendly, secure and productive Colour MFP series – TASKalfa 7353ci and 8353ci – will astonish you. Thanks to its newly designed 10.1" touch panel, accessing all features and getting exactly the results you need, is very intuitive and simple.

**TASKalfa 7353ci****A3 Colour Multifunctional****65/73 ppm for A4 (Colour/BW)****1,200 x 1,200 dpi resolution**

TASKalfa 7353ci

Specifications

GENERAL

KYOCERA TASKalfa Laser Colour Multifunctional, HyPAS™ solution platform
Operation panel: Full colour 10.1 inch TFT (1,024 × 600 dot) touch panel
Engine speed: Colour 65ppm/monochrome 73ppm, Colour 32 ppm/monochrome 36ppm A3 per minute, Duplex print speed: Colour 65 ppm/monochrome 73 ppm A4
Resolution: 1,200 dpi × 1,200 dpi multilevel: equivalent to 4,800 dpi × 1,200 dpi, 600 × 600 dpi (scan/copy)
Warm-up timer: 44 seconds or less
Time to first print: Approx. 5.3 Monochrome/6.3 Colour seconds or less
Time to first copy: Approx. 5.4 Monochrome/6.2 Colour seconds or less
CPU: Freescale QorIQ T1042 (Quad Core) 1.2GHz
Memory: Standard 4.5GB (CPU 2GB/ASIC 2GB/DP relay 0.5GB)
Standard interfaces: Standard interface: USB 2.0 (Hi-Speed), 4 × USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPsec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots, for optional internal print server or for optional fax system, Slot for optional SD Card, NFC tag
Integrated accounting: 1,000 accounts
Dimensions (W × D × H): 750 mm × 822 mm × 1,234 mm
Weight: Approx. 182kg
Power source: AC 220–240 V, 50/60 Hz
Power consumption: Copy/Print Mode: Mono 1,310 W/Colour 1,360 W; Low Power Mode: 110 W; Ready Mode: 120 W; Sleep Mode: 1 W
Noise (sound pressure level: ISO 7779/ISO 9296): Copying/Printing: 69 dB(A) L_{PA}
 Stand-by: 56 dB(A) L_{PA}
Safety standards: TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.
Input capacity: Multi-purpose tray: 150 sheets, 60–256 g/m² (Banner 135–165 g/m²), A3+, A3, A4, A5, A6, B5, Ledger, Letter, Legal, Folio, Custom (98 × 148 to 297 × 432 mm), Banner max. 305 × 1,220 mm;
 Standard universal paper cassette: 2 × 500 sheets, 60–256 g/m², A3+, A3, A4, A5, B5, Ledger, Letter, Legal, Folio;
 High-capacity paper deck: 2 × 1,500 sheets, 60–256 g/m², A4, B5.
 Max. input capacity with options: 7,650 sheets A4
Duplex: Standard Duplex unit: 60–256 g/m², A5R–305 × 457 mm
Output capacity: Standard job separator tray 70 sheets; optional copy tray (D): upper 100 sheets, lower 250 sheets; max. optional output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE
Emulations: PCL6 (PCL-XL/PCL-5e), KPDL 3 (PostScript 3 compatible), PDF, Requirement: KPDL3 setting, XPS/OpenXPS, PPML

Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 79 Outline fonts, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality

COPY FUNCTIONS

Max. original size: A3/Ledger – Minimum A6R(StatementR)

Continuous copying: 1–9,999

Zoom range: 25–400% in 1% steps

Preset magnification ratios: 5 Reductions/5 Enlargements

Exposure mode: Auto, manual: 16 steps

Image adjustments: Text + Photo, Photo, Text, Map, Printed document

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, Skip blank page, ID card copy

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan (WIA Driver Network)

Scan speed: (A4, 300 dpi, Dual Scan) 220 images per minute; (A4, 300 dpi, Simplex Scan) 120 images per minute

Scan resolution: 600 × 600 dpi, 400 × 400 dpi, 300 × 300 dpi, 200 × 400 dpi, 200 × 200 dpi, 200 × 100 dpi; 256 greyscales per colour

Max. scan size: A3, Ledger, Banner up to 2,200 mm

Original recognition: Text, photo, text + photo, light text/ fine line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, OOXML (OCR)

Features: Colour scan, Auto Colour Select, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip, Specified colour removal

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission time: Max. 3 seconds (JIBG)

Scanning speed: 2.0 seconds or less

Address book: 2,000 entries

Fax resolution: Normal: 200 × 100 dpi, Fine: 200 × 200 dpi, Superfine: 200 × 400 dpi, Ultrafine: 400 × 400 dpi, 600 × 600 dpi

Maximum original size: A3, Ledger, Banner up to 1,600 mm

Compression method: JIBG, MMR, MR, MH

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast, optional internet fax, dual fax with second fax system 12

CONSUMABLES

Average continuous toner yield in accordance with 6% coverage A4.

TK-8739K, TK-8739Y, TK-8739M, TK-8739C Toner Kit: Microfine toner black for 85,000 pages A4; Microfine toner Yellow for 40,000 pages A4; Microfine toner Magenta for 40,000 pages A4; Microfine toner Cyan for 40,000 pages A4

WT-861 Waste Toner Bottle: 150,000 sheets (Continuous print of 5% original (calculated as Mono/Colour=6:4))

Staples: SH-10 for BF-730/BF-9100, 3 × 5,000; SH-12 for DF-710, 3 × 5,000; SH-14 for DF-7130, 5 × 5,000

OPTIONS

Fax System 12

PF-730(B) Paper feeder: 2 × 500 sheets, 60–256 g/m²; A5R–305 × 457 mm, folio

PF-740(B) Paper feeder: 2 × 1,500 sheets, A4, 60–256 g/m²; A4, B5, Letter

PF-7120 Paper feeder: 3,000 sheets, 60–256 g/m²; A4, B5

PF-7130 Paper feeder: Multiside Tray, 1 × 500 sheets

DF-710 Document finisher: Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730 attachment), max. 60–300 g/m², max. B5R–305 × 457 mm;

Sub-tray: 200 sheets A4, 60–300 g/m², A6R–305 × 457 mm;

Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5–305 × 457 mm

DF-7130 Document finisher: Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-9100 attachment), max. 52–300 g/m², max. B5R–305 × 457 mm; Sub-tray: 200 sheets A4; 52–300 g/m², A6R–305 × 457 mm, Stapling up to 100 sheets A4 or 50 sheets A3 at 3 positions

PH-7C/PH-7D Punch unit: for DF-7110/DF-7130, 2-hole/4-hole/Swedish type, 60–256 g/m², A5R–A3

MT-730(B) 7-Bin Mailbox sorter: for DF-7110, 7 bins × 100 sheets A4, 50 sheets A3/B4, 60–163 g/m²

BF-730 for DF-7110 Booklet and tri-folding unit: Half folding: 60–256 g/m²; A3, B4, A4R; Booklet: max. 16 sheets (64 pages, 60–90 g/m²); Non-staple folding: max. 5 sheets (60–90 g/m²); Tri-folding: max. 5 sheets (60–90 g/m²) or max. 13 sheets (91–105 g/m²);

60–90 g/m²) 3 sheets (91–105 g/m²)

BF-9100 for DF-7130 Booklet and tri-folding unit: Half folding: 52–256 g/m²; A3, B4, A4R; Booklet: max. 20 sheets (80 pages, 60–90 g/m²) or max. 13 sheets (91–105 g/m²); Non-staple folding: max. 5 sheets (60–90 g/m²) or max. 13 sheets (91–105 g/m²); Tri-folding: 5 sheets (60–90 g/m²) or max. 13 sheets (91–105 g/m²)

Copy tray (D): upper tray 100 sheets, lower tray 250 sheets

USB IC Card Reader + Card Authentication Kit (B):

Supports various authentication card keys.

NK-7120: Numeric keypad

Keyboard Holder 10

UG-33: ThinPrint support

UG-34: Emulation (IBM Proprinter/EPSON LQ-850/Diablo 630)

Banner Guide (A): Banner paper feeding guide up to 10 sheets

Optional interfaces:

IB-35: Direct Wi-Fi Interface

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)

IB-51: Wireless Lan (802.11b/g/n)

The TASKalfa 7353ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 7353ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.





PO Box 1167
 North Cairns 4870
 Ph- 4080 2000
 Fax- 4080 2020
 info@evolvecairns.com.au
 www.evolvecairns.com.au

KYOCERA Document Solutions Partner

DECEMBER2019DSTASKALFA7353CI/VER1.1

KYOCERA Document Solutions Australia
 Ph: 13 59 62
 www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand*
 Ph: 0800 459 623
 www.kyoceradocumentsolutions.co.nz



kyoceradocumentsolutions.com.au