

OCCASIONAL DEEP CLEANING - PORCELAIN INTERNAL

Always follow manufacturers guidelines – these can be downloaded from the relevant product page on our website. We always recommend conducting a test in a discreet area prior to a full application of the product. Wear appropriate clothing and protective wear, such as gloves and glasses.

Porcelain tiles are extremely durable; however, it is recommended to maintain them correctly to keep them looking their best. There is no rule on the frequency, it comes down to usage and personal preference. Lithofin is our preferred brand for sealing and maintenance products. Their comprehensive range of products have been rigorously tested for their compatibility with both natural stone and porcelain for internal and external applications - as such, we have used and sold Lithofin's products to protect and maintain our products for over twenty years.

What you will need:

- Lithofin Intensive Cleaner (approx coverage: 50 to 300m² when used diluted)
- Microfibre Mop
- Stiff Brush
- White Towel / Wet Vac

For a deep floor clean, we recommend using the Lithofin Intensive Cleaner, designed to remove stubborn dirt, oil and grease. Begin by testing the product on two affected tiles using the below method. If there is no change, please contact the technical team at Lithofin who will be able to advise further.

1. To work out the correct ratio of product to water for your floor, we recommend testing the product on a tile in a discreet area with a ratio of 1:10. Apply generously and leave the product on for 8-10 minutes - scrubbing every minute with a stiff brush.
2. Rinse twice with clear water and towel dry or wet vac the tile before assessing the results. If you are not satisfied, increase the ratio of product to water and test again. We do not recommend using this product neat. Work in small controlled sections (2-3m² at a time).

If watermarks or limescale remains in bathrooms, we recommend using the Lithofin Ceramic Cleaner, designed specifically to remove the build up of limescale, rust, grease deposits and soap scum from porcelain tiles. Begin by testing the product on an affected tile using the below method. If there is no change, please contact the technical team at Lithofin who will be able to advise further.

1. Depending on the stubbornness of the dirt, dilute the product up to 1:15 and apply it to the affected tiles with a wet sponge. Allow the product to work briefly, then rinse well with water. In order to protect cement-based grout lines, wet the surface prior to application and use the product only in diluted form.

Lithofin technical helpline: 01962 732 126

Always keep pets and children away from any treated areas until the product has been removed.