



SPECIFICATIONS ON OPPOSITE SIDE.



19 OZ VINYL

01 Light Blue



02 Royal Blue



03 Red



04 White



05 Orange



06 Yellow



08 Tan



09 Gray



10 Maroon



11 Purple



12 Black



13 Navy Blue



14 Kelly Green



15 Dark Green



19 OUNCE, DOUBLE-COATED LAMINATED VINYL

porter[®]
www.PorterAthletic.com



porter®

190Z VINYL

DOUBLE-COATED, LAMINATED

Fabric Specifications

Total Weight: 19oz/yd²
Testing Method: ASTM D3776

Base Fabric:
9 x 9 x 1000 Denier Polyester

Grab Tensile (lb/in): 303(w) x 282(f)
Testing Method: ASTM D751

Trapezoidal Tear (lb): 76(w) x 100(f)
Testing Method: ASTM D751

Adhesion (lb/in): 9(w) x 10(f)
Testing Method: ASTM D751

Cold Crack, 3/8" Mandrel: -50° C
Testing Method: ASTM 2136

Porter uses a heavy-duty 19oz double-coated vinyl fabric on all curtains. The luxurious smooth finish is tear & abrasion resistant. Available in 14 UV resistant stock colors to compliment and coordinate with any school colors.

Features:

- Tear & Abrasion Resistant
- Rot & Fungus Resistant
- Mildew Resistant
- Dimensionally Stable
- Shrink Resistant
- UV Resistant



Flame Retardancy

NFPA 701-2010 TM2: Pass

ASTM E84: Class A or Class 1

CA Title 19-1237.1: Pass

CAL/ULC-S 109-03 LG & SM: Pass



Composition

Lead: Pass
Testing Method: GREENGUARD Certified

Phthalates: Pass
Testing Method: GREENGUARD Certified



Applications Include:

- Porter Curtains
- Floor Covering Material
- Mat Mover Slings

SMPLO0048035
(Replaces SMPLO0048021)