



LOOP/CLAMP FITTING PROVIDED FOR THIS END TO ADJUST CABLE TO DESIRED LENGTH

2" (5.08cm) WIDE WHITE HEM AT TOP AND SIDES

44'-0" (13.41m)

39" (1.00m)

SPRING-LOADED NET TENSIONER

4" (10.2cm) SQUARE #24 BLACK NYLON MESH NETTING

32'-0" (9.75m)

1/8" (3.2mm) DIAMETER 2000# (907.2kg) GALVANIZED AIRCRAFT CABLE WITH NYLON COATING (3/16" (4.8mm) O.D.)

ATTACHMENT LOOP WITH SWAGED CLAMP ONE END ONLY

TIE-OFFS (6)

ATTACHMENT LOOP WITH SWAGED CLAMP AND "S"-HOOK
1/4" (6.3mm) DIA. BRAIDED WHITE NYLON ROPE x 44'-0" (13.41m) Lg.

REVISION	DATE	Porter [®] No.
△		
△		CUSTOMER No.
△		
© COPYRIGHT 1991 PORTER ATHLETIC EQUIPMENT CO. ALL RIGHTS RESERVED		DATE 1-9-1991

02255-000
VOLLEYBALL NET

THIS PRINT IS THE PROPERTY OF PORTER ATHLETIC EQUIPMENT COMPANY AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION

Porter[®]
It's What the Pros Play On![®]
WORLD LEADER
IN QUALITY SPORTS EQUIPMENT
2500 S. 25th AVENUE
BROADVIEW, ILLINOIS 60155

DRAWING BY RJM
CHECKED BY EAS
PAGE No. V-2255

— 02255-000 VOLLEYBALL NET
32' x 39" (9.75m x 1.00m)
(FOR USE ON No. 851 AND 1951 SYSTEMS)

SPECIFICATIONS

PORTER No. 02255-000 VOLLEYBALL NET **(FOR USE ON No. 851 OR 1951 VOLLEYBALL SYSTEMS)**

Net shall be 32' x 39" (9.75m x 1.00m) to meet the latest requirement as specified by the USAV, NCAA and National Federation of State High School Associations.

Netting shall be high quality 4" square, #24 Black Nylon Mesh with a 2" wide, high quality vinyl coated polyester hem double stitched around entire perimeter of net. Top hem of net shall be furnished with a 1/8" diameter (2,000 lb. minimum breaking strength) galvanized aircraft cable 44'-0" in length with a nylon coating (3/16" O.D.) to protect against frayed cable. One end of cable to have loop with heavy swaged type fitting, other end to be provided with a special loop clamp fitting for providing the exact cable length for any volleyball system. Hems shall be provided with grommets and tie off cords to provide proper net tension.

Bottom of net shall be furnished with a 1/4" diameter braided white nylon rope equipped with a "Quik-Line", spring loaded pressure type locking line fastener to facilitate ease of installing and dismantling net system.