




MAINTENANCE & CARE INSTRUCTIONS FOR WALL PADS

SAFPAD™ WALL PADDING

Maintenance Guidelines

1. Periodically inspect wall pads for proper attachment to wall surface. If fasteners appear to be loose or damaged, tighten, repair, or replace as required.
2. The wall pad vinyl surface may be cleaned using a mild solution of 10% household detergent and warm water, or with a mild cleaning product such as Formula 409. If a more aggressive cleaning agent is required to remove stains, Power Foam sold by Rigmar Industries of Elk Grove Village, IL (1-800-323-0779) is recommended. Test application of this cleaner in an inconspicuous area of the wall pad before using it on the original stain, wipe residual cleaner with a water-dampened cloth after application. **Note: Do not use harsh solvent type cleaners. Solvent type cleaners cause cracking, crazing and general deterioration of vinyl materials.**
3. Inspect vinyl fabric for tears or holes. Repair with a color matching vinyl patch as soon as possible to prevent further tearing and exposure of the foam filler material. Industrial vinyl cement should be used to easily bond the vinyl patch to the wall pad. HH-66 Vinyl Cement sold by R-H Products Co., Inc. of Acton MA (978-897-8000) is recommended. Follow the manufacturer's instructions for application of the vinyl adhesive. Contact Porter Athletic for availability of matching color patch material.

 **WARNING:** This product can expose you to Urethane, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

SAVE THESE INSTRUCTIONS FOR FUTURE USE

Porter Athletics

601 Mercury Drive, Champaign IL, 61822
Phone: 217-367-8438 Fax: 217-367-8440
www.porterathletic.com