

Fire Resistant Cable Accessories



Description

RPS seals (commonly known as *Standard Seals*) are designed to be used in conjunction with our RGM glands.
 Manufactured and tested to BS EN 600702-2:2002 for ambient service temperatures of -20°C to 105°C
 Dependent on the cable size being used and in turn the gland size being used the pots are supplied in 20mm, 25mm, 32mm and 40mm

The RPS seal kit contains the following as standard	
ITEM DESCRIPTION	QTY
RPS POTS	20mm x 10, 25 32 & 40mm x2
SEAL OR STUB CAPS	20mm x 10, 25,32 & 40mm x 2
RMX SEALING COMPOUND	20mm x 3 sticks, 25,32 & 40mm 2 sticks
PVC SLEEVING	Dependent on cores – either 2 or 3 hanks of 1.5mtrs

Light Duty Cables		Heavy Duty Cables		Single Core Cables	
Cable ref	RPS needed	Cable Ref	RPS needed	Cable ref	RPS needed
2L1	RPS2L1	2H1.5	RPS2H1.5	1H2.5	RPS1H2.5
2L1.5	RPS2L1.5	2H2.5	RPS2H2.5		
2L2.5	RPS2L2.5	2H4	RPS2H4		
2L4	RPS2L4	2H6	RPS2H6		
3L1	RPS3L1	2H10	RPS2H10/25		
3L1.5	RPS3L1.5	3H1.5	RPS3H1.5		
3L2.5	RPS3L2.5	3H2.5	RPS3H2.5		
4L1	RPS4L1	3H4	RPS3H4		
4L1.5	RPS4L1.5	3H6	RPS3H6/25		
4L2.5	RPS4L2.5	3H10	RPS3H10/25		
		4H1.5	RPS4H1.5		
		4H2.5	RPS4H2.5		
		4H4	RPS4H4/25		
		4H6	RPS4H6/25		
		4H10	RPS4H10/25		

OTHER SIZES AVAILABLE ON REQUEST