

RUTLAND

TRUSTED SINCE 1883

HEARTH & HOME

PRODUCT CATALOG



140 YEARS OF INNOVATION

**WE OFFER A WIDE RANGE
OF QUALITY PRODUCTS TO
MAINTAIN, CLEAN, AND REPAIR
WOOD OR GAS STOVES,
FIREPLACES, HEARTHES, AND
CHIMNEYS, BOTH INDOORS
AND OUTDOORS, BACKED BY
140 YEARS OF EXPERTISE
AND INNOVATION.**

FIREPLACE & HEARTH

FIRE STARTERS	5
RAINBOW FLAME® CRYSTALS	5
CREOSOTE & SOOT REMOVERS	6-8
ACCESSORIES & GLOVES	9

MAINTENANCE

CLEANERS	10-11
CEMENTS & MORTARS	12-15
FIREBRICKS	15
GASKETS & INSULATION	16-17
HOME & CHIMNEY CARE	19
PAINTS & POLISHES	19-20
SEALANTS & ADHESIVES	21

BRUSHES & RODS

BRUSHES	23
RODS	24
ADAPTERS	24

INDEX

26

FIREPLACE & HEARTH



FIRE STARTERS

SAFE LITE® FIRE STARTER SQUARES

Easy to light - even when wet - and burn up to 10 minutes per square! Only 1 - 2 squares are needed to start a fire. Simply break off 1 - 2 squares and set them on wood or pellets. Light by touching a flame to the rough edge of a square. These environmentally friendly, non-toxic squares are made of compressed recycled wood chips, paper fiber, and wax. Will not flavor food.



- 50B Carton of 144 Squares (8 per case)
- 50C Carton of 24 Squares (24 per case)

USE: BBQ, Grills, Smokers



ONE MATCH® FIRE STARTER GEL

A thick, odor-free, gelled fire starter for quickly and easily starting any fire! Will not flavor food.



- 48 8 fl oz Bottle (12 per case)
- 49 16 fl oz Bottle (12 per case)
- 49Q 32 fl oz Bottle (12 per case)

USE: BBQ, Grills, Smokers



RAINBOW FLAME® CRYSTALS

RAINBOW FLAME® CRYSTALS

A family favorite - enjoy beautiful blue and green flames! Simply shake 1/2 cup, or toss the whole stick, onto a bed of hot coals. Not for use in gas units or in fires that will be used to prepare food.



- 715 1 lb Canister (12 per case)
- 715S 1.45 oz Long Toss-In Stick (24 per case)
- 715C 1.5 oz Short Toss-In Stick (36 per case)
- 715P Display Pack of 25 Rainbow Flame Toss-in Packets

USE: Fireplace, Fire Pit, Wood Stove, Outdoor, Indoor



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.

CREOSOTE REMOVER STICK

Makes chimney cleaning easier and helps prevent dangerous chimney fires! This remarkable formula turns creosote into a brushable ash in wood stoves, fireplace inserts, and free-burning fireplaces. Safe to use with all types of chimneys. Just toss entire tube onto a bed of hot coals. Tube burns safely to ash. Use 1 or more tubes per week as needed. Will not damage catalytic converters.

97S 3 oz Toss-In Stick (36 per case)



USE: Fireplace, Wood Stove



CREOSOTE REMOVER CANISTERS (3-PACK)

Contains 3 canisters to prevent creosote build-up in chimneys. Safe to use in all chimneys and wood-burning appliances. Simply toss one canister onto a bed of hot coals to turn sticky, tar-like creosote into brushable ash and prevent further build-up from occurring. Canisters burn safely to ash. Use 1 or more canisters per week as needed. Will not damage catalytic converters.

97G Three 3 oz Canisters (12 per case)

USE: Fireplace, Wood Stove



CREOSOTE REMOVER

Keeps creosote build-up at bay! Add 1-2 scoops to a fire once per week or more often as needed. Safe for use in all chimneys and wood-burning appliances. Will not damage catalytic converters.

97 1 lb Tub (12 per case)

98 2 lb Tub (6 per case)

USE: Fireplace, Wood Stove



PELLET STOVE CREOSOTE REMOVER

We've combined our trusted creosote removing technology with specially dried pellets to create an innovative creosote removing solution for pellet stove owners. This concentrated formula reduces dangerous creosote buildup. Use 2X/week during burn season.

98P 8 oz Box (12 per case)

98P03 3 lb Bag (5 per case)

98P04 4 lb Bag (3 per case)

98P05 5 lb Bag (4 per case)

98P08 8 lb Bag (3 per case)



USE: Pellet Stove, Fireplace, Wood Stove

LIQUID CREOSOTE REMOVER

Great for all stove and flue types, but best for pellet stoves where granules fall through the burner pan. Spray on an existing fire or pre-treat fuel before adding to a fire to make a chimney safer and more efficient.

97L 32 fl oz Spray Bottle (6 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Outdoor, Indoor



IMPORTANT! RECOMMENDED FREQUENCY OF SOOT/CREOSOTE REMOVER USE BASED ON WOOD TYPE BURNED



SOFTWOODS

- | | |
|------------|------------|
| Aspen | Basswood |
| Balsam Fir | Box Elder |
| Cedar | Cottonwood |
| Pine | Hemlock |
| Poplar | Willow |

LOW BTU

Burn at lower temperatures
Tend to be more porous woods with oils and resins that coat fireplace or stove in soot/creosote

RUTLAND Tip
Use soot/creosote remover 6-7 times per week



SOFT HARDWOODS

- | | |
|-------------|-----------|
| Birch | Hackberry |
| Cherry | Spruce |
| Douglas Fir | Sycamore |
| Elm | Walnut |
| Red Maple | Yew |

MID BTU

May contain some oils and resins that create some soot/creosote

RUTLAND Tip
Use soot/creosote remover 2-3 times per week



HARDWOODS

- | | |
|-------------|--------------|
| Ash | Apple |
| Beech | Dogwood |
| Hickory | Hawthorn |
| Oak | Mulberry |
| Sugar Maple | Osage Orange |

HIGH BTU

Burn at higher temperatures
Dry, dense woods that burn cleanly and create very little soot/creosote

RUTLAND Tip
Use soot/creosote remover 1 time per week

Estimates based on assumption that wood is burned daily during burn season. Actual BTUs may vary depending on region and specific type of wood. The potential exists for creosote buildup regardless of the wood type used if the wood is burning below 200°F

SOOT REMOVERS

KWIK-SHOT® SOOT STOPPER STICK

Reduces soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Just toss entire stick onto a bed of hot coals. Stick burns safely to ash. Stir and leave ashes for maximum effect. Use 1 or more sticks per week as needed.

100S 3 oz Toss-In Stick (36 per case)



USE: Fireplace, Wood Stove



KWIK-SHOT® SOOT STOPPER CANISTERS (3-PACK)

Contains 3 canisters to control soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Simply toss one canister onto a bed of hot coals to clean existing soot and prevent further deposits from forming. Canisters burn safely to ash. Use 1 or more canisters per week as needed.

100G Three 3 oz Canisters (12 per case)

USE: Fireplace, Wood Stove



SOOT SWEEP® SOOT DESTROYER®

Controls soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Add 1-2 scoops to a fire once per week or more often as needed.

100 1 lb Tub (12 per case)

100B 2 lb Tub (6 per case)

USE: Fireplace, Wood Stove



LOG BRIGHT® GAS LOG SOOT REMOVER

Spray on gas fireplace logs to safely remove and control future soot buildup, giving them a "like new" appearance. Easy to use, this spray-on cleaner does not require scrubbing or wiping off. Use on vented and vent-free liquid propane and natural gas units. Will not discolor ceramic logs or harm burners. Do not use on white birch or fiber logs.

570-6 16 fl oz Spray Bottle (6 per case)



USE: Gas Fireplace



ACCESSORIES

BURN INDICATOR

Monitors the performance of a wood- or coal-burning stove. See the potential for creosote build-up at a glance. Magnetically attaches to vertical, single-wall pipe or cooktop surface of a wood or coal stove. Indicates overheating or low-temperature creosote build-up hazard.

701-6 1 Magnetic Burn Indicator (6 per case)

USE: Wood Stove, Coal Stove, Indoor



STACK-N-STORE™ STEEL BRACKETS

Set of four heavy-duty, powder-coated corner brackets for building storage racks, shelves, and worktops in almost any size. Build a wood box to keep firewood off the ground to improve drying and to keep it away from pests and decay, or using more than one set, create storage shelves. Just screw or nail these brackets to any length of 2" x 4" lumber and the possibilities are endless!

30360R 4 Brackets Per Box (6 per case)



FIREPLACE GLOVES

Made from genuine cowhide leather and lined with cotton fabric. Gloves have a cuff that extends up the forearm for additional protection. Use for fireplaces, wood stoves, grills, and fire pits. These gloves are NOT rated fireproof or flame resistant. To prevent injury, avoid direct contact with open flames or smoldering embers. One size fits most. Red.

702 1 Pair of Gloves



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.

MAINTENANCE



CLEANERS

MULTI-SURFACE PRO CLEAN

This versatile cleaner conditions, cleans, and protects a variety of surfaces. The ammonia-free formula is perfect for use on glass, thermal glass, stainless steel, chrome, aluminum, porcelain, tile, ceramic range top, oven doors, sealed stone, kerosene heater glass, and fiberglass shower doors. Clean citrus scent. NOT for use on cars, windows, plastic (ex. microwave oven doors), plexiglass, stainless look or chrome look finishes.

185 8 fl oz Bottle (12 per case)



TSP CLEAN & PREP

Formulated for heavy duty cleaning. Removes grease, grime, soot, dirt, smoke, and stains, and prepares surfaces for repainting.

CLTSP01 1 lb Bag



STOVE, GRILL & HEARTH CONDITIONING GLASS CLEANER

Non-scratching formula consisting of micro-scrubbers that remove baked-on soot, creosote, carbon, and other mineral residues from glass doors of fireplace inserts, and coal-, oil-, and wood-burning stoves and pellet stoves. Ammonia-free. Leaves behind a protective silicone layer to make future cleanings even easier!

84 8 fl oz Bottle (12 per case)



WHITE-OFF® GLASS CLEANING CREAM

Specially formulated for the removal of white residue on gas log fireplace glass doors. Non-abrasive and easy to use, this glass cleaning cream does not scratch or cause micropitting. Ammonia-free.

565 8 fl oz Bottle (12 per case)



FIREPLACE & WOOD STOVE GLASS CLEANER

Formulated to remove smoke, soot, and creosote residue from glass doors of fireplaces and wood stoves. Spray-on cleaner does not contain dangerous acids or ammonia. Just spray on and wipe off - it's that easy! In no time at all, fireplace or stove glass will have that "like-new" appearance for continued enjoyment of leisure fires.

82 32 fl oz Spray Bottle (6 per case)



BRICK & STONE CLEANER

Removes stubborn creosote or soot build-up on bricks or stone surrounding a fireplace. Industrial strength solvent will penetrate and dissolve build-up on most any stone or sealed brick without use of dangerous acids. Can also be used on an asphalt roof to remove chimney smoke and grime.

83-6 16 fl oz Spray Bottle (6 per case)



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.



CEMENTS & MORTARS

NAME	CURE TYPE	STICKS TO MASONRY/METAL	INDOOR/OUTDOOR USE	TEMP RATING (F)	APPLICATION LAYER*
FIREPLACE MORTAR (63, 63B, 63G)	HEAT CURE	MASONRY	INDOOR	2000°	1/8" - 1/4"
BLACK FURNACE CEMENT (64A, 64C, 64, 65)	HEAT CURE	BOTH	INDOOR	2000°	UP TO 1/8"
STOVE & GASKET CEMENT (77, 78)	AIR DRY	BOTH	INDOOR	2000°	UP TO 1/8"
FIBERGLASS GASKET CEMENT (77E, 78E)	AIR DRY	BOTH	INDOOR	2000°	UP TO 1/8"
CHIMNEY MASONRY PATCH (89)	AIR DRY	MASONRY	BOTH	200°	1/8" - 1/2"
DRY MIX 211 (211)	AIR DRY	MASONRY	BOTH	2550°	1/16" - 1"
CASTABLE REFRACTORY CEMENT (600, 601)	AIR DRY	MASONRY	BOTH	2200°	1/2" - 9"
REFRACTORY CEMENT (610, 611)	HEAT CURE	MASONRY	INDOOR	2000°	UP TO 1/4"
STOVO (615)	HEAT CURE	BOTH	INDOOR	2000°	1/8" - 1/4"
PIPE INSULATING CEMENT (623)	AIR DRY	BOTH	INDOOR	300°	1/2" +

HEAT CURE: Allow to air-dry for 24 hours. Burn a low ~250°F fire for about 2 hours, then build the fire up to ~500°F for an additional hour. Learn more about heat curing and watch demonstrations:



Scan to view our Cements & Mortars Minute Clinic.

E-Z SPREAD FIBERGLASS STOVE GASKET CEMENT

Designed to be the easiest gasket cement for affixing fiberglass gaskets to steel and cast iron. Very easy to spread and control application and will not expand or contract during continued use. Apply in layers of 1/8" or less. 2000°F temperature rating. New and improved, no longer requires heat cure. Black.

- 77E 2.3 fl oz Tube (12 per case)
- 78E 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



STOVE & GASKET CEMENT - THE ORIGINAL

This cement pulls double duty because not only can this cement adhere any fiberglass gasket to most any metal, it can also be used to fix those small cracks, pinholes, and leaks in a cast iron stove. Available in a handy squeeze tube or in a larger caulk gun-ready size, this cement will help restore a stove to safe and efficient operation. Apply in layers of 1/8" or less. 2000°F temperature rating. New and improved, no longer requires heat cure. Black.

- 77 2.3 fl oz Tube (12 per case)
- 78 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



REFRACTORY CEMENT

An ideal high-heat cement for masonry joints 1/4" or less. Pre-mixed, easy to trowel, and fiber reinforced, this cement can be used to set, bond, and repair cracked or broken firebricks in stoves, fireplaces, and furnaces as well as for building fireplace boxes. Its thick, smooth consistency makes this cement perfect for use as mortar between firebricks. Meets ASTM E136-04. 2000°F temperature rating. Requires heat cure. Buff.

- 610 64 fl oz Tub (6 per case)
- 611 128 fl oz Pail (2 per case)

Heat Cure Required



USE: Fireplace, Wood Stove, Indoor



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.

CEMENTS

CASTABLE REFRACTORY CEMENT

An exceptionally strong dry-mix cement that chemically sets and dries as hard as brick. Just add water! Perfect for casting into custom designs because it holds its shape while drying. Can even be used as the sole material when casting a solid stove bed or outdoor oven. 2200°F temperature rating. Does not require heat cure! Cast up to 9" depth. Color may vary.

- 600 12.5 lb Pail (2 per case)
- 601 25 lb Pail (1 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Outdoor, Indoor



FURNACE CEMENT

Premixed and ready to use, this is one of the easiest cements to apply. Use this smooth consistency cement to bond and seal metal to metal or metal to masonry joints less than 1/8". Repair a crack, seal the collar to the top of a wood stove, or seal between firebricks and prefabricated fireplace. Use anywhere a quality high-temperature adhesive is required for furnaces, firebrick repair, filling gaps, sealing joints, or gluing ceramic logs. Adheres to metal, stone, and firebricks, creating a permanent smoke- and gas-tight seal. 2000°F temperature rating. Heat cure required.

- 64A 8 fl oz Tub (12 per case)
- 64C 10.3 fl oz Cartridge (12 per case)
- 64 16 fl oz Tub (12 per case)
- 65 32 fl oz Tub (6 per case)

USE: Fireplace, Wood Stove, Indoor



MORTARS

STOVO® STOVE MORTAR

Ready-to-use, premixed, and general-purpose for repairing or relining firebrick in interior stoves, furnaces, boilers, incinerators, Franklin stoves, barbecues, and fireplaces. Adheres to metal or masonry and will prevent air and gas leaks around flue and chimney joints, ash pit doors, and small cracks between bricks and linings. Apply in layers 1/4" or less and allow to air dry for 24 hours between layers. 2000°F temperature rating. Requires heat cure. Buff.

- 615 32 oz Tub (6 per case)

USE: Fireplace, Wood Stove, Indoor



MORTARS

FIREPLACE MORTAR

Perfect for repairing small chips or cracked firebrick, re-pointing mortar joints between firebricks, and bonding firebricks together. Adheres masonry to masonry for brick, firebrick, and stone. Use for cracks 1/8" deep or less. If deeper, apply multiple layers of ~1/8" and allow 24 hours to dry between layers. Easy to apply with a caulking gun and will last for years. Sets as hard and as strong as firebrick after curing and can withstand the high temperatures produced by a wood fire. 2000°F temperature rating. Requires heat cure.

- 63 Black 10.3 fl oz Cartridge (12 per case)
- 63B Buff 10.3 fl oz Cartridge (12 per case)
- 63G Gray 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



DRY MIX 211®

A refractory mortar ideal for joining or repairing masonry flue tile in any gas or wood fireplace and wood, coal, or pellet stove chimney. Just add water, mix, and trowel on to seal and join flue tiles. It can also be used as a parge coating (thin over-coat) when building fireboxes to give a fireplace a nice, even, dark gray finish. Meets NFPA 211 Standards and NYSCMA Tek 4.0 Specifications. 2550°F temperature rating. Does not require (but is stronger with) heat cure. If applying in layers, do not exceed 1" per layer and allow 24 hours to dry between layers. Dark Gray.

- 211 10 lb Pail (4 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Outdoor, Indoor



FIREBRICKS

FIREBOX BRICKS

These firebricks can be used to build new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). Color may vary. They can also be used to line a fire pit in the backyard or anywhere else a brick is needed that can withstand high temperatures up to 2700°F. Each brick measures 9" x 4.5" x 1.25".

- 603-1 6 Bricks per case - 2000°
- 604-1 6 Bricks per case - 2700°

USE: Outdoor, Indoor





NEW!

PREMIUM SELF-ADHESIVE CERAMIC GRILL REPLACEMENT GASKET

Our braided fiberglass gasketing is engineered to provide superior sealing, protection, and longevity. Additionally, RUTLAND's industrial grade gaskets feature 3M adhesive technology enabling the gaskets to endure more than five clean burns. Kits come in two sizes: 12 feet of gasket material to replace old gaskets on mini, small, medium and large, and 17 feet of gasket material to replace old gaskets on XL and XXL Big Green Eggs or similarly sized smokers.

- 99N12 12' (15 per case)
- 99217 17' (15 per case)
- 99N12G 12' (15 per case)
- 99217G 17' (15 per case)



Scan to view installation instructions.



PIPE INSULATING CEMENT

Insulates pipes to conserve energy. This dry-mix cement forms an easy-to-use paste when mixed with water. Can be used on pipes, fittings, tanks, and boilers to keep them insulated. Adheres to most masonry and metal surfaces. 300° temperature rating. Does not require heat cure.

- 623 2 lb Bag (12 per case)



FIBERGLASS INSULATION

An insulation strip with a peel-off, self-adhesive backing that is ideal for forming a smoke- and gas-tight seal between a fireplace insert and existing masonry. For the best performance, replace insulation every time the insert is removed for cleaning. Rated to 250°F.

- 105 10' Roll (6 per case)



GRAPHO-GLAS® STOVE GASKETS

Graphite impregnated, braided fiberglass gasketing engineered to provide superior sealing, protection, and longevity. Also resist abrasion, creosote and soot adhesion, and temperatures up to 1000°F. Used by major stove manufacturers and to replace worn-out gaskets in wood and coal stoves or fireplace inserts. Annual replacement of stove gaskets ensures a tight seal for maximum airtight operation and efficiency.

KITS (Includes Gasket & Fiberglass Stove Gasket Cement) (6 per case)

- 95A-6 7' x 5/16" Rope
- 95-6 7' x 5/8" x 3/16" Flat
- 95W-6 7' x 3/4" x 1/4" Flat
- 96-6 7' x 3/8" Rope
- 96N-6 7' x 1/2" Rope
- 96W-6 7' x 5/8" Rope
- 99-6 7' x 3/4" Rope
- 99N-6 7' x 7/8" Rope



Also available by the foot upon request.
Call 800-544-1307 for pricing.

BAGGED (Cement not included)

- 90 7' x 5/8" x 3/16" Flat
- 91 7' x 3/8" Rope
- 91N 7' x 1/4" - 5/16" Rope
- 92 5' x 1/2" - 5/8" Rope

- 92W 7' x 3/4" Rope
- 94N 5'4" x 7/8" Rope
- 94 6' x 1" Rope

SPOOLS

- 720 157' x 5/8" x 3/16" Flat
- 721 200' x 5/16" Rope
- 721N 200' x 1/4" Rope
- 722 132' x 3/8" Rope
- 723 88' x 1/2" Rope
- 723W 100' x 7/16" Rope

- 724 65' x 5/8" Rope
- 725 47' x 3/4" Rope
- 725W 40' x 7/8" Rope
- 726 25' x 1" Rope
- 516GG 75' x 5/16" Griddle Gasket

WHITE FIBERGLASS GASKETS SPOOLS

- 721P 200' x 5/16" Rope
- 726P* 25' x 1" Rope
- 78LA* 25' x 7/8" Lopi Rope

GASKET SPOOL DISPLAY

Holds 5-6 gasket spools with convenient measuring tape. Black.

- 108E 24" x 12"

*Special Order, Please Call



STOVE WINDOW GASKETS

Designed to securely seal stove window glass in stove doors and openings. Peel off protective paper and wrap self-adhesive tape over the glass edge. No additional cement is needed. Available in Black with graphite or White.

- 93 Black 4'6" x 11/16" Bagged (12 per case)
- 727 Black 80' x 11/16" Spooled (1 per case)
- 727P White 80' x 13/16" Spooled (1 per case)
- 729 Black 90' x 13/16" Spooled (1 per case)



Scan to view our video illustrating how to replace a stove door gasket.



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.



HOME & CHIMNEY CARE

CONCRETE & MASONRY PATCH *not for sale in California*

Weather-resistant and easy to apply. This multi-purpose cement patch dries hard and tough with a natural concrete finish. Useful for repointing and making small repairs to broken mortar in chimneys, steps, sidewalks, foundations, windowsills, and fireplace faces. Not high-heat rated.

89 10.3 fl oz Cartridge (12 per case)



USE: Outdoor, Indoor



WATER GLASS CEMENT FLOOR SEALER

This unique formula is a multi-use sealant and adhesive. When diluted, it becomes an excellent stain-resistant concrete sealant against oils. Use full-strength for an effective and inexpensive adhesive for sealing gaskets, cartons, and applying labels.

146 1 gal Jug (4 per case)



USE: Indoor



PAINTS

HI-TEMP PAINTS

Provide both a beautiful flat black finish as well as durability to any stove or grill, and will look great for years while keeping rust at bay. Use outdoors or indoors. Adhere to steel, cast iron, aluminum, and brick, and are great for grills, stoves, smokers, stove pipes, fireplace inserts, furnaces, barbecues, mailboxes, lampposts, fireplace tools, brass, firebrick, and chimney caps. Flat Black.

PREMIUM 1400°F BRUSH-ON PAINT WITH LOW VOC

81V 16 fl oz Can (6 per case)



1200°F HI-TEMP PAINTS

80 12 fl oz Spray Can (12 per case)

81 16 fl oz Can* (6 per case)

**Product 81 not for sale in California*

USE: Outdoor, Indoor



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.

POLISHES

STOVE POLISH *not for sale in California*

Transforms old, dull, cast iron stoves into like-new appearance! Combines three different waxes with some of the blackest pigments to renew and protect cast iron. Non-toxic and non-flammable, this polish can be buffed to a deep lustrous glow, leaving cast iron looking better than new. Prevents deterioration to the exteriors of stoves, grills, ornamental ironwork, and heating accessories even during extended storage. Not for use on painted, powder-coated, stainless, raw, or sandblasted steel. Black.

70 2.3 fl oz Tube (12 per case)



USE: Outdoor, Indoor



LIQUID STOVE & GRILL POLISH *not for sale in California*

Protects cast iron and steel heating and cooking appliances from getting dull and rusty. Apply polish and buff to a high luster to restore that like-new appearance. Safe to use – non-flammable and non-toxic. One bottle should lightly polish an average sized, free-standing wood stove or a large grill. Not for use on painted, powder-coated, sand-blasted, stainless, or raw steel surfaces. Black.

72 8 fl oz Bottle (12 per case)



USE: Outdoor, Indoor



WILLIAM'S® STOVE POLISH *not for sale in California*

Brings a low-luster, dark gray finish to any unpainted cast iron appliances. Easy to apply. Buff after drying. Can also be used on wood and coal stoves, barbecues, hibachis, iron pots, iron kettles, and grills. Not for use on painted, powder-coated, sand-blasted, stainless, or raw steel surfaces. Dark Gray.

WI-00710 2.3 fl oz Tube (12 per case)



USE: Outdoor, Indoor



SEALANTS

SEAL IT RIGHT® FLEXIBLE LATEX SEALANT *not for sale in California*

A non-permanent seal that expands and contracts with heat variations. For use with metal and aluminum. Use to install and maintain direct vent appliances, gas-burning systems, pellet stoves, and metal flues on wood and coal stoves. Easily removed for cleaning and inspection. Not an adhesive. 800°F continuous temperature rating. Black. Does not require a heat cure.

641C 2.3 fl oz Tube (12 per case)

641 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Indoor, Outdoor



HIGH HEAT SILICONE SEALANT

A great solution for sealant needs – seals off gases and smoke permanently, with limitless uses in the home or on job sites. Use to seal fireplace inserts, repair solar panels, or seal a chimney cap to withstand wind, rain, and hot smoke. Available in 600°F RTV and 500°F RTV temperature ratings and two colors (Red and Black) as well as Clear. Does not require a heat cure.

600°F RTV

600°F RTV temperature rating and available in Red and Black.

76R Red 10.3 fl oz Cartridge (12 per case)

76B Black 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Indoor, Outdoor



500°F RTV

500°F RTV temperature rating and available in Black and Clear. Choose from a handy 2.7 fl oz tube for small repairs or a 10.3 fl oz caulk gun cartridge for larger jobs.

76 Black 10.3 fl oz Cartridge (12 per case)

76A Black 2.7 fl oz Tube (12 per case)

76C* Clear 10.3 fl oz Cartridge (12 per case)

76CT* Clear 2.7 fl oz Tube (12 per case)



*Food safe, FDA regulation #21 CFR 177.2600.



BRUSHES & RODS

CHIMNEY SWEEP® BRUSHES

CHIMNEY SWEEP® WIRE CHIMNEY BRUSHES

Designed with the homeowner in mind, these brushes have an open, single spiral construction with 6" of fill, plated shafts, and 1/4" NPT threading for easy coupling with fiberglass rods or pull rings. Oil-tempered spring wire. Use in masonry and metal liners. Use in cool chimney only. Use with RUTLAND® Rods 10624, 10672, and KRK-18 on page 24.



Tip: Be sure to match the fitting of brushes and rods (NPT - NPT or 1/4-20 - 1/4-20). Use a **Rutland Reducer** to allow the use of mismatched brushes and rods!

ROUND WIRE

- 16406 6" Round (4 per case)
- 16407 7" Round (4 per case)
- 16408 8" Round (4 per case)
- 16409 9" Round (1 per case)
- 16410 10" Round (1 per case)

SQUARE WIRE

- 16506 6" Square (4 per case)
- 16507 7" Square (4 per case)
- 16508 8" Square (4 per case)
- 16510 10" Square (1 per case)
- 16511 11" Square (1 per case)
- 16512 12" Square (1 per case)

RECTANGULAR WIRE

- 36531 6" x 10" Rectangular (1 per case)
- 16532 7" x 11" Rectangular (1 per case)
- 16533 8" x 12" Rectangular (1 per case)

CHIMNEY SWEEP® ROUND POLY CHIMNEY BRUSHES

Specially designed for stainless steel, liners, and stove pipes. These sturdy poly brushes have 6" of fill and are acid resistant. Fittings are 1/4" NPT threading. Use in masonry and metal liners. Use in cool chimney only. Use with RUTLAND® Rods 10624, 10672, and KRK-18 on page 24.

- 16906 6" Round Poly (4 per case)
- 16908 8" Round Poly (4 per case)

CHIMNEY SWEEP® PELLET STOVE & DRYER VENT BRUSHES

Designed to clean both pellet stove vents and dryer vents. Brushes can easily navigate a sharp turning radius without getting caught in elbows. Brush filament is 0.020" poly. For light cleaning only. For heavier buildups, use RUTLAND® Pellet Stove Brushes PS-3, PS-4, or PS-5, shown below.

- 17409 3" Brush with 10' Flexible Handle (4 per case)
- 17410 4" Brush with 10' Flexible Handle (4 per case)
- 17419 3" Brush with 20' Flexible Handle (4 per case)
- 17420 4" Brush with 20' Flexible Handle (4 per case)

CHIMNEY SWEEP® PELLET STOVE BRUSHES

Made with poly bristles and available in 3", 4", and 5" round sizes. Heavy-duty ball tip guides brushes through narrow offsets and bends. Designed for heavy cleaning. Fittings are 1/4-20 thread. Use with RUTLAND® Rods 25P-5 and PSR-20 on page 24.

- PS-3 3" Round Poly (4 per case)
- PS-4 4" Round Poly (4 per case)
- PS-5 5" Round Poly (1 per case)



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.

FIBERGLASS CHIMNEY BRUSH EXTENSION RODS

Designed with the DIY homeowner in mind. Rods are available individually in lengths of 4' and 6' and use 1/4" NPT threading to connect to a chimney brush. Attach to a RUTLAND® Chimney Sweep® Wire or Poly Brush to clean a chimney from the top down or up through the open fireplace. The fiberglass is flexible enough to handle slight offsets, but not enough to bend around sharp corners. Cleaning in an up-and-down motion with these rods will provide the power necessary for a satisfactory result.

- 10624 4' Individual Rod Bends <90° (24 per case)
- 10672 6' Individual Rod Bends 90° (24 per case)
- KRK-18 18' Kit (Six 3' Rods) Bends 45° (5 per case)



FLEXIBLE POLY PELLET STOVE RODS

Poly rods designed to easily maneuver through 30° and 45° offsets, 0.250" diameter and 1/4-20 thread. Use with RUTLAND® Chimney Sweep® Pellet Stove Brushes.

- 25P-5 5' Individual Rod Bends 360° (10 per case)
- PSR-20 20' Kit (Eight 2.5' Rods) Bends 360° (5 per case)



PULL RING - HOMEOWNER

Designed for the DIY homeowner to attach to RUTLAND® Extension Rods to provide an attachment point for ropes to pull RUTLAND® Chimney Sweep® Cleaning Brushes through a chimney during cleaning. Available with 1/4" NPT threading.

- 16202 1/4" NPT (12 per case)
- W38PTL 3/8" NPT (12 per case)



REDUCER

Allows use of mismatched brushes and rods. Female connectors on both sides will adapt a brush and rod set to match each other. Product 1438 converts 1/4" NPT to 3/8" NPT, and 1439 converts 1/4" NPT to 1/4-20 threading.

- 1438 1/4" to 3/8" NPT (12 per case)
- 1439 1/4" NPT to 1/4-20 Threading (5 per case)



PRODUCT #	PAGE #	PRODUCT #	PAGE #	PRODUCT #	PAGE #
25P-5	24	96N-6	17	721P	17
48	5	96W-6	17	722	17
49	5	97	6	723	17
49Q	5	97G	6	723W	17
50B	5	97L	7	724	17
50C	5	97S	6	725	17
505	5	98	6	725W	17
63	15	98P	7	726	17
63B	15	98P03	7	726P	17
63G	15	98P04	7	727	17
64	14	98P05	7	727P	17
64A	14	98P08	7	729	17
64C	14	99-6	17	1438	24
65	14	99N-6	17	1439	24
70	20	99N12	16	10624	24
72	20	99N17	16	10672	24
76	21	100	8	16202	24
76C	21	100B	8	16406	23
76CT	21	100G	8	16407	23
76A	21	100S	8	16408	23
76B	21	105	16	16409	23
76R	21	108E	17	16410	23
77	13	146	19	16506	23
77E	13	185	10	16507	23
78	13	211	15	16508	23
78E	13	516GG	17	16510	23
78LA	17	565	11	16511	23
80	19	570-6	8	16512	23
81	19	600	14	16532	23
81V	19	601	14	16533	23
82	11	603-1	15	16906	23
83-6	11	604-1	15	16908	23
84	11	610	13	17409	23
89	19	611	13	17410	23
90	17	615	14	17419	23
91	17	623	16	17420	23
91N	17	641	21	30360R	9
92	17	641C	21	36531	23
92W	17	701-6	9	CLTSP01	10
93	17	702	9	KRK-18	24
94	17	715	5	PS-3	23
94N	17	715C	5	PS-4	23
95-6	17	715P	5	PS-5	23
95A-6	17	715S	5	PSR-20	24
95W-6	17	720	17	W38PTL	24
96-6	17	721	17	WI-00710	20
		721N	17		



RUTLAND

TRUSTED SINCE 1883

CONTACT RUTLAND CUSTOMER SERVICE

TO SPEAK WITH ONE OF OUR EXPERIENCED PROFESSIONALS!

800.544.1307 . 802.775.5519 . Fax 802.775.5262 . sales@rutland.com . rutland.com
7 Crabtree Road . Jacksonville, IL 62650

Copyright © Rutland
RC-2320



CONNECT WITH US!



@RUTLANDPRODUCTS



CHECK OUT OUR RUTLAND PRODUCTS YOUTUBE CHANNEL FOR PRODUCT AND HOW-TO VIDEOS!

