




Assembly Instructions:

Tip: For a professional look, always stitch out next to previous stitch on the same side of the stitch;



correct

incorrect

1. The leather bag is sewn inside out, with the smooth sides of the leather together, then turned right side out. Place the bag parts together with the rough sides facing out to start. **(Fig. A)**
2. Using the needle and waxed thread, stitch up through the second hole of one corner, leaving 2-3" to tie off later. Stitch down through the first hole of both parts, and back up through the second hole. **(Fig. B)**
3. Continue your running stitch until you reach the top hole on the opposite side. When you've reached this point, add a second stitch to the top two holes to strengthen the stress point. Stitch back to the starting point and add a second stitch at the two starting holes for strength. **(Fig. C)**. Tie the two ends of the thread in a square knot and trim the extra length. Turn the bag right side out.



1. Fold the lace drawstring in half and thread through the two holes on one side of the bag, weaving in and out to the opposite side of the bag. **(Fig. D)**
2. Next, fold the closure circle in half and thread one end of lace through one set of overlapping holes. Repeat with the other end of lace and the second set of overlapping holes. Tie the ends of the lace in a knot outside of the bag. The closure on the drawstring allows you to open or tightly close the bag and protect the contents inside. **(Fig. E)**



WARNING: CHOKING HAZARD
Small parts. Not for children under 3 years.

Find tutorials, tips, patterns and project ideas on realeather.com