




Assembly Instructions:

1. Starting with 44" of lace, glue one end of lace to the metal ring and clamp. Apply a small amount of glue as you go, wrapping the entire ring while aligning the lace and pulling tightly as you go. Clamp in place to dry. **(Fig. A)**
2. Tie one end of sinew to the ring. Tie the sinew to the ring again 1" to the right, using a single half hitch. **(Fig. B)**. Continue tying off around the ring until you reach the starting point, pulling the sinew tight after each half hitch.
3. Next, tie a half hitch between each span of the first row of sinew. Pull tightly as you proceed around the circle. Continue around the circle until you have an opening of only about half inch in the center. Tie off and trim excess sinew. **(Fig. C)**
4. Cut one 12" length and two 8" lengths of lace. Attach one of the 8" lengths to the top of the hoop as a hanger using a larks head knot. **(Fig. D)**. Attach one of the 12" lengths to the bottom of the hoop using a larks head and add beads and feathers as desired. Place a drop of glue at the base of the bead to secure feather. Attach one of the 8" lengths to the bottom of the hoop using a larks head, add beads and feathers, tie a knot at the end to secure. **(Fig. E)**



⚠ WARNING: CHOKING HAZARD - Contains small parts.
Not for children under 3 years.

Find tutorials, tips, patterns and project ideas on realeather.com