# POCKET DOOR PRO

## HENDERSON

### 120

### DATA SHEET

12.50

FWT

Designed with a high quality aluminium cavity frame, Pocket Door Pro is a robust, professional hardware solution that allows doors to slide into a cavity wall with ease. The system is ideal for educational buildings, homes, hospitals, hotels and offices. Also suitable for areas such as bathrooms and ensuites, where space may be limited, or disability access is required.

For ease of installation the aluminium cavity frame comes with push together parts. The system can be supplied with a soft stop which catches the door at the end of its travel and gently pulls it into position.

The system is also available in bi-parting and automated variants.

#### **Pocket Door Pro Kit Includes:**


- Robust, high quality aluminium cavity frame
- Push-together parts for easy and rapid installation


#### Your Kit can be enhanced with:

- Dual Soft Close (up to 120kg)
- (SOFTHP120) • Liner Kits (LKH/120, LKH/125, BILKH/120, BILKH/125)

### You will also need:

- Flush pulls
- (385/S, 385EDGE/S, 53/S, 390/S, 571/S, 60SQ/S)







PW = DW - 50 Key:

OW = Overall Width DH = Door Height PH = Passage Height FWT = Finished Wall Thickness

OW = (Door width x 2) + 30

OH = Overall Height DW = Door Width PW = Passage Width





OW = (Door width x 2) + 30

#### **Kit and Door Specification** Short Code Max. Door Width Max. Door Height **Door Thickness** Max. Door Weight **Finished Wall Thickness** PDKPROH1 610mm 1981mm 35-45mm 120kg 120mm or 125mm PDKPROH2 686mm 1981mm 35-45mm 120kg 120mm or 125mm PDKPROH3 762mm 1981mm 35-45mm 120kg 120mm or 125mm PDKPROH4 838mm 35-45mm 120kg 120mm or 125mm 1981mm PDKPROH6 826mm 2040mm 35-45mm 120mm or 125mm 120ka PDKPROH7 726mm 120mm or 125mm 2040mm 35-45mm 120kg PDKPROH10 930mm 2315mm 35-45mm 120kg 120mm or 125mm

P C HENDERSON LTD Durham Road, Bowburn, t: +44 (0) 191 377 7345 Co. Durham,

DH6 5NG

**UK SALES** e: sales@pchenderson.com **w:** www.pchenderson.com

REV 2 Feb-23

