

## Safety Data Sheet

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ECO-UV, EUV5-2MG  
ECO-UV, EUV5-5MG  
ECO-UV, EUV5P-7MG

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

#### 1.3. Details of the supplier of the safety data sheet

Manufacture's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: + 81-53-484-1224 FAX: + 81-53-484-1226

E-mail:

Revised date: 09-Jan-2024

#### 1.4. Emergency telephone:

### 2. Hazard identification

#### 2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

|   |             |
|---|-------------|
| Acute toxicity (oral)                                 | Category 4  |
| Acute toxicity (dermal)                               | Category 4  |
| Skin corrosion/irritation                             | Category 2  |
| Serious eye damage/eye irritation                     | Category 1  |
| Sensitisation (Skin)                                  | Category 1A |
| Reproductive toxicity                                 | Category 2  |
| Specific target organ toxicity (Repeated exposure)    | Category 2  |
| Hazardous to the aquatic environment (AcuteHazard)    | Category 1  |
| Hazardous to the aquatic environment (Chronic Hazard) | Category 1  |

#### 2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word:

Danger

**Hazard Statement:**

Harmful if swallowed.  
Harmful in contact with skin.  
Causes skin irritation.  
Causes serious eye damage.  
May cause an allergic skin reaction.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Very toxic to aquatic life with long lasting effects.

**Precautionary statements — Prevention:**

Do not handle until all safety precautions have been read and understood.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statements — Response:**

IF ON SKIN: Wash with plenty of soap and water.  
IF exposed or concerned: Get medical advice/attention.

**2.3. Other hazards**

## Potential Health Effects:

|                         |  |
|-------------------------|--|
| Eyes:                   | Causes severe eye injury which may persist for several days.   |
| Skin:                   | Contact with skin may cause irritation, swelling or redness, allergic sensitization.   |
| Inhalation:             | Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and irritate nose, throat/respiratory system. |
| Ingestion:              | May cause injury of mouth, throat, and stomach.  |
| Chronic Health Hazards: | Repeated skin contact may cause a persistent irritation or dermatitis.   |
| Carcinogenicity:        | None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)  |
| Others:                 | No information.  |

### 3. Composition/information on ingredients

Chemical nature: mixture

| Composition  | CAS No.     | % By Weight | GHS Classification  |
|--|-------------|-------------|---|
| Benzyl acrylate                                    | 2495-35-4   | 20-30       | Skin Irrit. 2: H315<br>Skin Sens. 1B: H317<br>Aquatic Acute 1: H400<br>Aquatic Chronic 1: H410  |
| Hexamethylene Diacrylate                           | 13048-33-4  | 20-30       | Skin Irrit. 2: H315<br>Eye Irrit. 2: H319<br>Skin Sens. 1: H317   |
| Morpholine, 4-(1-oxo-2-propenyl)                   | 5117-12-4   | 10-20       | Acute Tox. 4: H302<br>STOT RE 2: H373<br>Eye Dam. 1: H318<br>Skin Sens. 1: H317   |
| 2-Propenoic acid, 2-phenoxyethyl ester             | 48145-04-6  | 5-10        | Skin Sens. 1A: H317<br>Repr. 2: H361<br>Aquatic Chronic 2: H411   |
| 2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester    | 7328-17-8   | 5-10        | Acute Tox. 4: H302<br>Acute Tox. 3: H311<br>Skin Irrit. 2: H315<br>Eye Irrit. 2: H319<br>Skin Sens. 1A: H317<br>Aquatic Chronic 2: H411 |
| 2-Propenamide, N,N-dimethyl-                       | 2680-03-7   | 5-10        | Acute Tox. 3: H301<br>Acute Tox. 3: H311<br>Eye Damage 1: H318  |
| Ethyl phenyl(2,4,6-trimethylbenzoyl) phosphinate   | 84434-11-7  | 1-5         | Skin Sens. 1B: H317<br>Aquatic Chronic 2: H411  |
| Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide | 162881-26-7 | 1-5         | Aquatic Chronic 4: H413   |
| 4-Methoxyphenol                                    | 150-76-5    | <1          | Acute Tox. 4: H302<br>Eye Irrit. 2: H319<br>Skin Sens. 1: H317  |

† For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

- Eyes:** In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open during flushing. Call a physician.
- Skin:** In case of contact, immediately flush with plenty of water while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

---

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Eyes: Causes severe eye injury which may persist for several days.
- Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.
- Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and irritate nose, throat/respiratory system.
- Ingestion: May cause injury of mouth, throat, and stomach.

#### 4.3. Indication of any immediate medical attention and special treatment needed

no information

### 5. Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

Flash Point: > 94deg.C

#### 5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

#### 6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

#### 6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

#### 6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

### 7.3 Specific end use(s): Inkjet Printing

## 8. Exposure controls/ personal protection

### 8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Hexamethylene Diacrylate:

[Long term exposure] 24.5 mg/m<sup>3</sup>

[Short term exposure] no hazard identified

— Morpholine, 4-(1-oxo-2-propenyl):

[Long term exposure] 132.24 mg/m<sup>3</sup>

[Short term exposure] 132.24 mg/m<sup>3</sup>

— 2-Propenoic acid, 2-phenoxyethyl ester:

[Long term exposure] 12 mg/m<sup>3</sup>

[Short term exposure] hazard unknown (no further information necessary)

— 2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester:

[Long term exposure] 2.6 mg/m<sup>3</sup>

[Short term exposure] no hazard identified

— 2-Propenamide, N,N-dimethyl-:

[Long term exposure] 0.207 mg/m<sup>3</sup>

[Short term exposure] no hazard identified

— Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate:

[Long term exposure] 4.93 mg/m<sup>3</sup>

[Short term exposure] no hazard identified

— Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

[Long term exposure] 21 mg/m<sup>3</sup>

[Short term exposure] hazard unknown (no further information necessary)

### 8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

**Hand protection:**

Employee must wear appropriate protective impervious gloves to prevent contact with the ink. Recommended Chemical Protective Gloves are EN420/374 approved ethylene vinyl alcohol (EVOH) Gloves and Laminate gloves. Laminate gloves are made by cutting and then heat-sealing patterns of various hand sizes from laminated sheets of EVOH sealed between layers of polyethylene.

**Eye protection:**

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

**Skin protection:**

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

**Hygiene measures:**

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

**Environmental exposure control:**

Avoid release to the environment.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|   |                      |
|---|----------------------|
| Appearance:                                   | Magenta Liquid       |
| Odour:  | Characteristic odour |
| Odour threshold:                              | Not defined          |
| pH:   | Not applicable       |
| Melting point/freezing point:                 | No data available    |
| Initial boiling point and boiling range:      | No data available    |
| Flash point:                                  | > 94deg.C            |
| Evaporation rate:                             | No data available    |
| Flammability (solid, gas)                     | Not applicable       |
| Upper/lower flammability or explosive limits: | No data available    |
| Vapor pressure:                               | No data available    |
| Vapor density:                                | No data available    |
| Relative density:                             | 1.0-1.1              |
| Solubility(ies):                              | Slightly soluble     |
| Partition coefficient: n-octanol/water:       | No data available    |
| Auto-ignition temperature:                    | No data available    |

ECO-UV, EUV5-2MG  
 ECO-UV, EUV5-5MG  
 ECO-UV, EUV5P-7MG

G\_3.0

2024/01/09

|   |                   |
|---|-------------------|
| Decomposition temperature:                | No data available |
| Viscosity:                                | No data available |
| Explosive properties:                     | No data available |
| Oxidizing properties:                     | No data available |
| Volatile organic compounds (VOC) content: | 0.047 g/L         |

## 9.2 Other information

No information.

## 10. Stability and reactivity

### 10.1 Reactivity:

High temperatures and UV light may cause rapid polymerization.

### 10.2 Chemical stability:

Stable under normal temperature.

### 10.3 Possibility of hazardous reactions:

Not expected.

### 10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

### 10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

### 10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity:

Morpholine, 4-(1-oxo-2-propenyl)

LD50 (oral) : 588mg/kgbw, LD50 (dermal): >2000mg/kgbw, LD50 (Inhal.): no data available

2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester

LD50 (oral) : ca.1106mg/kgbw., LD50 (dermal): no data available, LD50 (Inhal.): no data available

2-Propenamide, N,N-dimethyl-

LD50 (oral) : >215-<464mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): no data available

4-Methoxyphenol

LD50 (oral) : no data available, LD50 (dermal): no data available, LD50 (Inhal.): no data available

#### Serious eye damage/eye irritation:

Causes serious eye damage.

- Morpholine, 4-(1-oxo-2-propenyl)
- 2-Propenamide, N,N-dimethyl-

Causes serious eye irritation.

- Hexamethylene Diacrylate
- 2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester
- 4-Methoxyphenol

**Skin corrosion/irritation:**

Causes skin irritation.

- Benzyl acrylate
- Hexamethylene Diacrylate
- 2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester

**Respiratory or skin sensitisation:**

May cause an allergic skin reaction.

- Benzyl acrylate
- Hexamethylene Diacrylate
- Morpholine, 4-(1-oxo-2-propenyl)
- 2-Propenoic acid, 2-phenoxyethyl ester
- 2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester
- Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate
- 4-Methoxyphenol

**Germ cell mutagenicity:**

no data available.

**Reproductive toxicity:**

Suspected of damaging fertility or the unborn child.

- 2-Propenoic acid, 2-phenoxyethyl ester

**Carcinogenicity:**

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

**Specific target organ toxicity - single exposure, (STOT-SE):**

no data available.

**Specific target organ toxicity - repeat exposure, (STOT-RE):**

May cause damage to organs through prolonged or repeated exposure.

- Morpholine, 4-(1-oxo-2-propenyl)

**Aspiration hazard:**

no data available.



---

## 12. Ecological information

### 12.1. Toxicity:

Very toxic to aquatic life.

- Benzyl acrylate

Very toxic to aquatic life with long lasting effects.

- Benzyl acrylate

Toxic to aquatic life with long lasting effects.

- 2-Propenoic acid, 2-phenoxyethyl ester
- 2-Propenoic acid, 2-(2-ethoxyethoxy)ethyl ester
- Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

May cause long lasting harmful effects to aquatic life.

- Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

### 12.2. Persistence and degradability:

No data available

### 12.3. Bioaccumulative potential:

No data available

### 12.4. Mobility in soil:

No data available

### 12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

### 12.6. Endocrine disrupting properties:

No data available

### 12.7. Other adverse effects:

No data available

## 13. Disposal considerations

### 13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of under the same conditions as the product itself.

Recommended waste code: 08 03 12\* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10\* (packaging, the residues of dangerous substances or hazardous waste contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be disposed of in the same way as the substance.

## 14. Transport information

### 14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA : 3082

### 14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA : Environmentall hazardous substance, liquid, n.o.s.

### 14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA : 9

### 14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA : III

### 14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA : Environmentally hazardous substance, liquid, n.o.s.

### 14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA : Transport and storage of the product in accordance with general precautions and instructions mentioned in this SDS.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

## 15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006

This product has not carried out any Chemical Safety Assessment yet.

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

## 16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H311: Toxic in contact with skin.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.

ECO-UV, EUV5-2MG  
ECO-UV, EUV5-5MG  
ECO-UV, EUV5P-7MG

G\_3.0  
2024/01/09

- 
- H400: Very toxic to aquatic life.
  - H410: Very toxic to aquatic life with long lasting effects.
  - H411: Toxic to aquatic life with long lasting effects.
  - H413: May cause long lasting harmful effects to aquatic life.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.