

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Seapower Cleaner and Wax
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Product category PC31 Polishes and wax blends
- Process category
PROC10 Roller application or brushing
PROC0 Other
- Environmental release category
ERC10a Widespread use of articles with low release (outdoor)
- Application of the substance / the mixture
See our technical datasheet for application of this product.
Maintenance product for cleaning and waxing
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
fax +31-(0)297-342078
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!
See manufacturer

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

(R)-p-mentha-1,8-diene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 68551-19-9 EINECS: 271-369-5 Reg.nr.: 01-2119491311-45-0000	alkanes, C12-14-iso- ⚠ Asp. Tox. 1, H304	25-50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 112-80-1 EINECS: 204-007-1 Reg.nr.: under C&L Inventory	oleic acid, pure ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 9

Revision: 27.02.2017

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 2)

CAS: 63148-62-9 EC number: 613-156-5 Reg.nr.: under C&L Inventory	Polydimethylsiloxane Eye Irrit. 2, H319	2.5-10%
CAS: 5989-27-5 EINECS: 227-813-5 Index number: 601-029-00-7 Reg.nr.: 01-2119529223-47	(R)-p-mentha-1,8-diene Flam. Liq. 3, H226 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-10%
CAS: 110-91-8 EINECS: 203-815-1 Index number: 613-028-00-9 Reg.nr.: 01-2119496057-30	morpholine Flam. Liq. 3, H226 Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	≤ 2.5%

- Additional information:
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
 - General information: Immediately remove any clothing soiled by the product.
 - After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
 - After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
 - After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
 - After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 3)

- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
see labelling instructions.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

110-91-8 morpholine

WEL	Short-term value: 72 mg/m ³ , 20 ppm Long-term value: 36 mg/m ³ , 10 ppm
	Sk

- DNElS

67-63-0 propan-2-ol

Inhalative	Long-term - systemic effects, worker	500 mg/m ³ (Werker/Worker)
------------	--------------------------------------	---------------------------------------

- Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 4)

- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Colour:	According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Not determined.
- Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	82 °C
- Flash point: 40 °C
- Flammability (solid, gas): Not applicable.
- Ignition temperature: 255 °C

(Contd. on page 6)

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.927 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/ water:	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic at 20 °C:	100 s (ISO 6 mm)
· Solvent content: Organic solvents:	11.5 %
VOC content:	11.5 %
	VOC content: 106.6 g/l / 0.89 lb/gl
· 9.2 Other information	No further relevant information available.

*

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

*

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

68551-19-9 alkanes, C12-14-iso-

Oral	LD50	>5 mg/l (rat)
------	------	---------------

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 9

Revision: 27.02.2017

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 6)

Dermal	LD50	>2000 mg/kg bw (rabbit)
Inhalative	LC50	>5.3 mg/l (rat)
67-63-0 propan-2-ol		
Oral	LD50	5045 mg/kg bw (rat)
Dermal	LD50	12800 mg/kg bw (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
112-80-1 oleic acid, pure		
Oral	LD50	74000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg bw (Guinea pig)
	LD50	230 mg/kg (mouse)
		2 mg/kg (rat)
63148-62-9 Polydimethylsiloxane		
Oral	LD50	≥17000 mg/kg (rat)
Dermal	LD50	≥5000 mg/kg bw (rabbit)
5989-27-5 (R)-p-mentha-1,8-diene		
Oral	LD50	4400 mg/kg bw (rat)
	LD50	5600-6600 mg/kg (mouse)
	LD50	4400 mg/kg (rat)
Dermal	LD50	5000 mg/kg bw (rabbit)
110-91-8 morpholine		
Oral	LD50	1050 mg/kg bw (rat)
	LD50	90 mg/kg (Guinea pig)
		720 mg/kg (mouse)
		1050 mg/kg (rat)
Dermal	LD50	500 mg/kg bw (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye irritation.
- Respiratory or skin sensitisation
May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity
Based on available data, the classification criteria are not met.
- Carcinogenicity
Based on available data, the classification criteria are not met.
- Reproductive toxicity
Based on available data, the classification criteria are not met.
- STOT-single exposure
Based on available data, the classification criteria are not met.
- STOT-repeated exposure
Based on available data, the classification criteria are not met.
- Aspiration hazard
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 9

Revision: 27.02.2017

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 7)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes:
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number
 - ADR, IMDG, IATA
 - 14.2 UN proper shipping name
 - ADR
 - IMDG
 - IATA
- UN1993
1993 FLAMMABLE LIQUID, N.O.S., ENVIRONMENTALLY HAZARDOUS
FLAMMABLE LIQUID, N.O.S.
FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), Naphtha (petroleum), hydrotreated heavy)

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 9

Revision: 27.02.2017

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 Flammable liquids.
· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No
· Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Flammable liquids.

· EMS Number: F-E, S-E

· Stowage Category A

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging:
30 ml
Maximum net quantity per outer packaging:
1000 ml

· IMDG

· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging:
30 ml
Maximum net quantity per outer packaging:
1000 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS

GB

(Contd. on page 10)

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	10-25
- Waterhazard class:
Water hazard class 3 (Self-assessment): extremely hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
- Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 9

Revision: 27.02.2017

Trade name: Epifanes Seapower Cleaner and Wax

(Contd. of page 10)

DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids - Category 2
Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Skin Corr. 1B: Skin corrosion/irritation - Category 1B
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
Skin Sens. 1: Skin sensitisation - Category 1
STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
Asp. Tox. 1: Aspiration hazard - Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
* Data compared to the previous version altered.

GB