

Epifanes Accelerator for Paint & Varnish

Additive to reduce the open time of traditional paints & varnishes

Type	Air drying	
Base	Wood oil	
Fields of application	General: Additive for traditional one-component paints and varnishes.	
	For exterior use:	add no more than 5-7%. This will not affect the gloss, elastic and longevity of the paint or varnish.
	For interior use:	i.e. on chairs, tables, floors, etc. up to 50% can be added to Epifanes Clear Gloss Varnish for a harder, scratch resistant finish.
	Used pure:	As sealer for resinous wood, bleeding pigments and for 2-3 coats per day can be applied on natural wood where a slight yellowing is less important.
Colour	Yellowish Transparent	
Gloss	High gloss	
Density	0,90kg/dm ³	
Viscosity	40 seconds DIN-cup 6 mm.	
Solids contents	58 +/- 2 vol. %	
VOC - level	375 grams/liter	
Packing	500ml. - 1000ml.	
Shelf life	In closed container stored in a dark location between 5-25°C., approx. 3 years.	
Conditions during application and drying	Temperature	minimal 8°C. - maximum 30°C.
	Relative air humidity	minimal 50% - maximum 75%
Thinner for brush applications	Epifanes Brushthinner for Paint & Varnish	
Thinner for spray applications	Epifanes Spraythinner for Paint & Varnish	
Application	Do not use wet-on wet	
Application tools	Soft, longhaired brush (oval or full style) Conventional air spray	
Theoretical coverage (pure product)	18m ² per litre @ 30 µm dry filmthickness	
Practicle coverage	Dependent on application	