

FLEXIBLE SOLAR PANEL MONOCRYSTALLINE



AIMS POWER™

www.aimscorp.net


230 WATT



Features:

- Crack resistant film
- Efficient
- Durable

Panel Layer:



Mechanical Characteristics

Cell Type & No.	Mono Cell (4x15)
Front Material	PET/ETFE
Junction Box	IP65 (Front Set/Back Set)
Connector	MC4 Compatible

Temperature Characteristics

NOCT	45±2°C
Temperature coefficient of Pmax	-0.38%/°C
Temperature coefficient of Voc	-0.29%/°C
Temperature coefficient of Isc	0.05%/°C

Electrical Characteristics Under STC*

Module	PV230SLIM
Maximum Power-Pmax (Wp)	230
Voltage at Maximum Power-Vmp (V)	17.4
Current at Maximum Power -Imp (A)	13.22
Open Circuit Voltage-Voc (V)	20.8
Short Circuit Current-Isc (A)	13.99
Module Efficiency- η_m (%)	20.1
Power Tolerance (W)	0/+3
Dimensions (inch, L×W×H)	58 × 30.5 × .12
Weight (lb)	8.3
Maximum System Voltage	1000VDC (IEC)
Operating Temperature	-40°C ~ +85°C
Maximum Series Fuse	20A

STC (Standard Testing Conditions) : Irradiance 1000/m², Cell temperature 25°C, AM 1.5

NOCT(Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient temperature 20°C, AM 1.5, Wind speed 1m/s

