



Installation Instructions

	Steel Top Hat Spacers	
	Suggested tools	Ramps or jack standsJackHand tools
	Safety Warnings	 Always support the vehicle with jack stands before working underneath Use only the parts supplied by RalliTEK to install this kit Check ALL the fasteners for tightness before and after road testing the vehicle Do not use an air impact wrench with reinstalling bolts as stripped threads may occur
	RalliTEK STEEL TO	OP HAT SPACER INSTALLATION
1.	Remove the struts from the vehicle; spring compressors are not necessary if only installing RalliTEK steel top hat spacers.	
2.	Install the front spacers on the struts. These spacers have alignment correction built into them, the right (passenger) side has a yellow dot on it, make sure that the studs are offset to the outside of the strut with the point in the RalliTEK logo and arrow pointing forward. The picture is showing installation on the right side strut.	
3.	Install the rear spacers on the struts; the rear spacers are the same left to right.	



Dedicated to improving vehicle fun, safety and performance

SI-022

4. Reinstall the struts on the vehicle while making sure the points on the RalliTEK logo or arrow on the spacer point toward the front of the vehicle. It is recommended to get an alignment done after installing RalliTEK top hat spacers.



WARRANTY

One Year Limited Warranty

RalliTEK warrants to the original purchaser that the parts manufactured and/or sold by RalliTEK (the Product) is free from defects in material and workmanship under normal use. RalliTEK warrants that the Product will per-form substantially in accordance with the specifications set forth in the documentation provided with it. The above express warranties are made for a period of the lesser of 12,000 miles or 12 months from the date the Product is installed in your vehicle.

Any improper use, operation beyond capacity, substitution of parts not approved by **RalliTEK** in writing, any alteration or repair by others, or any removal, defacing or altering of the identification shall void this warranty. There is no warranty on high-performance or race related parts due to the nature of usage.

The purchaser shall notify **RalliTEK** at 888-773-1212 of any defect within the warranty period no later than thirty (30) days after purchaser discovers the defect. Should any failure to conform to this warranty appear within the warranty period, RalliTEK shall, on notification, correct the nonconformity at its option, either by repairing any defective part, or by making available, FOB RalliTEK plant, a repaired or replacement part. The purchaser must insure any defective item being returned because RalliTEK does not assume risk of loss or damage while in transit. No payment or reimbursement shall be made for installation, removal, transportation or other charges. The remedies set forth in this instrument are exclusive, and the liability of RalliTEK with respect to any sale shall not exceed the price of the product on which the liability is based.

EXCEPT AS STATED OTHERWISE IN THIS WARRANTY, **RalliTEK** MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUD-ING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. RalliTEK shall not in any case be liable for special, incidental, consequential, indirect, or other similar dam-ages arising from any breach of these warranties even if RalliTEK or its agent has been advised of the possibility of such damages. Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to you.

This warranty is governed by the laws of the State of Oregon.

