



Notified body N° 0075

EC-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° 0075/1929/162/05/16/0581

Is given to the following model of personal protective equipment :

Issued to : NANTONG SAFECHOICE JINKE GLOVE CO.,LTD

NO.333,JIANGXIN ROAD,DONGAN INDUSTRIAL
ZONE,RUDONG,JIANGSU PRO,CHINA.226400

CHINA

Distributor : /

Product reference : DOTS GLOVE

Description :

PPE Type : *Protective gloves against mechanical risks.*

Reference standard : *EN 388 : 2003.*

Category : *II*

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the complete certificate N°0075/1929/162/05/16/0581.

Issued in Lyon by Lionel Gaudillere
Head of CE marking

Date of issue : May 31st, 2016



In application of the Directive ref 89/686/EEC of the 21th December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decree N°92-765, 766 and 768 of the 29th July 1992 concerning the transposition of this Directive into French law. CTC is notified by decree of the Ministry of work of the 20th December 2010 and is registered under the number 0075 in OJEU.



4 rue Hermann Frenkel 69367 Lyon cedex 07 FRANCE
Tel : 33 472 761 010 - Fax : 33 472.761.000 - email : ctclyon@ctcgroupe.com – www.ctc.fr
Comité professionnel de développement économique cuir chaussure maroquinerie
Siret 77564972600160 – code NAF 9412Z – TVA FR 88775649726





In application of the Directive ref. 89/686/EEC of the 21st of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29th of July 1992 concerning the transposition of this Directive into French law,

CTC

4,rue Hermann Frenkel - 69367 Cedex 07 - France
Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupe.com - www.ctc.fr

authorized by decrees of the Ministry of Work, Employment and Health of the 20th of December 2010,
registered under the number 0075, published in OJEC, delivers :

EC-TYPE EXAMINATION CERTIFICATE 0075/1929/162/05/16/0581

To the following model of personal protective equipment :

- * reference of the model : DOTS GLOVE
- * protective glove against mechanical risks.
- * Manufacturer :

NANTONG SAFECHOICE JINKE GLOVE CO.,LTD

**NO.333,JIANGXIN ROAD,DONGAN INDUSTRIAL ZONE,RUDONG,JIANGSU
PRO,CHINA.226400**

CHINA

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

Drawn up in Lyon, on May 31st, 2016

Issued by Lionel GAUDILLERE



NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R. 4313-38 of the French Code of Work.

1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index : 01

Reference : DOTS GLOVE

Basic Model

Dated : MAY, 2016

10G POLYESTER LINER, WITH PVC DOTS ON PALM

Available sizes :

6 7 8

Visual description :



Material :

	Color	Material	Gauges	Thickness
PALM	White	POLYESTER	10	
	BLue	PVC DOTS		
BACK	White	POLYESTER	10	
LINING				
CUFF	White	POLYESTER/ ELASTIC	10	
BINDING	blue, black, orange, grey, purple, white, red, yellow, green, brown	POLYESTER		

2. PROTECTION SCOPE

Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:

- * EN 420:2003+A1:2009 - General requirements for gloves and test methods
- * EN 388:2003 - Protective glove against mechanical risks
- * At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)
- * This product is a category II.

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	CTC	Other
EN 420	S160504480 S150705019 S160301002	
Azo	S160504480 S150705019 S160301002	
EN 388	S160504480	
OTHER	S160504480 (PAHs TIN CAD) S160200846 (DMFu) S160403404_2 (DMFu)	

Performance levels offered against mechanical risks (EN 388:2003) are:

Abrasion resistance	Blade cut resistance	Tear strength resistance	Puncture resistance
2	2	4	X

The levels of performance have been measured on the palm

« X » means that the test hasn't been performed ; no protection is required

3. MARKING

Each glove is clearly marked with the following information:

- * Logo of the authorized representative:
- * **CE** marking
- * reference of the model: DOTS GLOVE
- * size
- * pictogram for mechanical risks followed by the performance levels
- * information pictogram

Marking example:

SafeChoice
DOTS GLOVE



NANTONG SAFECHOICE JINKE GLOVE CO.,LTD

MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	DOTS GLOVE
Technical file index	:	01
Last update	:	MAY, 2016

IDENTIFICATION

Reference of the product : : DOTS GLOVE
Basic model : :
Technical file index : : 01
Last update : : MAY, 2016

Manufacturer :

NANTONG SAFECHOICE JINKE GLOVE CO.,LTD

NO.333,JIANGXIN ROAD,DONGAN INDUSTRIAL ZONE,RUDONG,JIANGSU
PRO,CHINA.226400

CHINA

tel : 0510-86871166
fax : 0510-86871799

Factory :

NANTONG SAFECHOICE JINKE GLOVE CO.,LTD

NO.333,JIANGXIN ROAD,DONGAN INDUSTRIAL ZONE,RUDONG,JIANGSU
PRO,CHINA.226400

CHINA

tel: 0510-86871166
fax: 0510-86871799

BEIHAI KINGSKY ENTERPRISE CO.,LTD

RM 1304,UNIT 4,BLDG.B,CHENGSHILIJING,NO.1 MID XINAN
AVENUE,BEIHAI,GUANGXI,CHINA

CHINA

tel: 86-779-3831933
fax: 86-779-3201479

GLOVE DESCRIPTION

Glove description :

10G POLYESTER LINER,WITH PVC DOTS ON PALM

Visual description:



Available sizes :

Minimum length of glove (mm)	Sizes
220	6
230	7
240	8

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
PALM		White	POLYESTER	150g/m2	10	
		BLue	PVC DOTS			
BACK		White	POLYESTER	150g/m2	10	
LINING						
CUFF		White	POLYESTER/ ELASTIC	205g/m2	10	
BINDING		blue, black, orange, grey, purple, white, red, yellow, green, brown	POLYESTER			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 4

PH of glove and lining is greater than 3.5 and lower than 9.5 : yes

Chromium VI lower than the detection limit : conform

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2003

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	2
Tear strength resistance	4
Puncture resistance	X

The levels of performance have been measured on the palm
« X » means that the test hasn't been performed ; no protection is required

TEST REPORTS

Laboratory	CTC	Other
EN 420	S160504480 S150705019 S160301002	
Azo	S160504480 S150705019 S160301002	
EN 388	S160504480	
OTHER	S160504480 (PAHs TIN CAD) S160200846 (DMFu) S160403404_2 (DMFu)	

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :

Logo **CE**

Glove's reference : DOTS GLOVE

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example :

SafeChoice
DOTS GLOVE



Method of marking on the glove :

printed on the back

Packaging :

12pairs/dozens, 10dozens/ctn

MEANS OF CONTROL

Operation Process and Quality Requirement of Marking and Cutting Material

- 1st After getting the cotton fabric, pick out and disuse the spoiled fabric, the dirty fabric and the hard fabric.
- 2nd Pack the fabric according to the color, then mark and cut.
- 3rd Avoid every crack and mesh. Patching is strictly forbidden.
- 4th Each dozen must match consistently by color. In case there are exceptions, match them by pair.
- 5th The piece number of each style and each dozen must be guaranteed to be accurate.
- 6th Losing shape or lacking edges is strictly forbidden.
- 7th Carry on the operation in accordance with the quality requirement in the manufacture order.
- 8th Make sure each bundle is neat and tight, indicate the labor number and then hand over to the distribution room.
- 9th Unconditionally make up or exchange for the insufficient materials, otherwise may make fine processing.
- 10th Any return of fabric must be taken back in the unified time the distribution room arranged.

Mechanical Stitching Operation Process and Quality Requirement

- 1st Stitch length: three to four stitches each CM.
- 2nd The straight edge of the little finger must be vertical to the thumb. Rabbet between 1.5 CM and trace on sides.
- 3rd Set the middle item vertical to the four fingers and 2CM beside the opening. Side walks the line.
- 4th Set the elastic vertical to the middle position between the middle item and side. The two threads are away from each other in 3--4 MM, and must symmetrically be parallel.
- 5th Rabbet 5MM to meet the palm. Side walks the line, again walls the parallel line .the distance requires 3MM width.
- 6th Stitch the middle finger:
Make sure the opening between the little finger mould and the middle finger mould matches that of the middle finger. The clamp is 6to 7cm long. Stitch it between the little finger and the ring finger to the middle finger and the first finger. The saw side is 2MM.
- 7th Stitch the thumb:
Make sure the top of the thump match the thumb mould. the clamp is 1.5 to 2CM long. Stitch it on the opening of the thumb. The saw side is 2MM.stitch it round.
- 8th Gathering:
The first finger mould gathers with the back of the first finger. the lower line gathers with the thumb. The sew side is 3MM.stitch it straight.
- 9th Apron:
Start with the little finger cloth. Rabbet in a distance between 2to 3MM, 7to 10 MM long and set level. Put the middle place between the crown and the cuff into the button of the lining. Finish till the little finger mould with double thread. Stitch round around the crown. As to another one, start with the little finger mould; end with the little finger back cloth.
- 10th Gathering fingers:
Start from the first finger, end in the position 1/3 of the cuff, during which, make sure the cloth match the leather mould, sew side 2to 3 MM, stitch the top round. Then rabbet the fingers accordingly .for another one ,start from the position 1/3 of the cuff and mark ,then back to the first finger top and end. Both hands link by the cuff.

INSTRUCTION FOR USE

NANTONG SAFECHOICE JINKE GLOVE CO.,LTD

NO.333,JIANGXIN ROAD,DONGAN INDUSTRIAL ZONE,RUDONG,JIANGSU PRO,CHINA.226400
CHINA

Glove reference : DOTS GLOVE

Available sizes : 6 7 8

Glove description :

10G POLYESTER LINER,WITH PVC DOTS ON PALM

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (OO75)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 4

Moreover, this glove has been designed for the following applications :



Application :

Mechanical hazard - EN 388



224X

Levels of performance

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	2	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	X	(on 4 maxi)

Protection limit :

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.