

# **Synthetic Slings Polyester Round Slings**





# **ENDLESS ROUNDSLINGS**

### Endless The Most Versatile Roundsling

## Features and Benefits

Maintains all the basic features plus...

#### **Promotes Safety**

 Load stability and balance can be achieved by spreading sling legs.

#### Saves Money

- · Wear points can be shifted to extend sling life.
- The most flexible style of sling. ٠

	Length How To Measure							
			END					
						JSLIN		
Rated Capacity* (lbs.)								
		Vertical	Choker	Basket @ 90°	Basket @ 45°			
Part			$\bigcirc$			Minimum Length		



ENDLESS ROUNDSLINGS												
			Rated Capacity* (lbs.)					Approximate Measurements				
			Vertical	Choker	Basket @ 90 <sup>°</sup>	Basket @ 45 <sup>°</sup>						
Part Number Color			$\bigcirc$	$\bigcup$		Minimum Length (ft.)	Weight (Ibs. / ft.)	Body Diameter Relaxed (in.)	Body Width at Load (W) (in.)	Minimum Hardware Dia.** (in.)		
AR1	Purple		2,600	2,100	5,200	3,600	1.50	.2	0.63	1.00	0.44	
AR2	Green		5,300	4,200	10,600	7,400	1.50	.3	0.88	1.38	0.63	
AR3	Yellow		8,400	6,700	16,800	11,800	3.00	.5	1.13	1.75	0.75	
AR4	Tan		10,600	8,500	21,200	14,000	3.00	.6	1.13	1.88	0.88	
AR5	Red		13,200	10,600	26,400	18,000	3.00	.8	1.38	2.00	1.00	
AR6	White		16,800	13,400	33,600	23,000	3.00	.9	1.38	2.13	1.13	
AR7	Blue		21,200	17,000	42,400	29,000	3.00	1.3	1.75	2.63	1.19	
AR9	Gray		31,000	24,800	62,000	43,000	3.00	1.7	2.25	3.25	1.50	
AR11	Brown		53,000	42,400	106,000	74,000	8.00	2.8	2.75	4.00	2.00	
AR12	Olive		66,000	52,800	132,000	93,000	8.00	3.4	3.13	4.63	2.13	
AR13	Black		90,000	72,000	180,000	127,000	8.00	4.3	3.63	5.25	2.50	

\*\* This is the minimum recommended diameter for the connection hardware to be used for a vertical hitch.

**A** WARNING

Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°. Refer to the Effect of Angle chart in the HELP section of this catalog.