

VT65MLSSHV



33.5" x 23.63" x 23.5" (H x W x D)

Freestanding counter height all-freezer capable of -25° C operation, with lock, wrapped stainless steel door and thin handle

Highlights:

-25° C operation for safe storage of temperature sensitive materials

Made in Europe

Factory-installed lock provides security you can count on

Product Features:

Slim counter height dimensions	24" footprint offers an easy fit
Manual defrost	Reduced temperature fluctuation with an energy efficient manual defrost system
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Adjustable thermostat	Dial thermostat for easy temperature management
Factory installed lock	Keyed lock for a secure interior
Stainless steel wrapped door	Durable design offers a professional look
Professional handle	Thin 14mm diameter on vertically set stainless steel handle
No internal fans	Static cooling system
Three removable storage baskets	Conveniently organize your items while keeping the temperature stable when the door is opened

VT65MLSSHV Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	115.0 lbs. (52 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101030869
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)

Temperature Range

