

HYDRA KOOL



SEAFOOD CASE WITH ICE PANS

CASES REQUIRE FLOOR DRAINS

DELI CASES - SEAFOOD

MEDIUM TEMPERATURE
TILT FORWARD FLAT
TEMPERED FRONT GLASS
REAR TEMPERED SLIDING DOORS
USED WITH ICE PANS

ICE PANS



MODELS

KFM - S F - (40,50,60,80,100,120) - S

KFM - S F - (40,50,60,80,100,120) - R




REMOTE AND SELF CONTAINED
404A REF - FORCED AIR REFRIGERATION
ALTERNATE REFRIGERANTS AVAILABLE BY SPECIAL ORDER



5659 Royalmount Ave.
Montreal, QC, Canada H4P 2P9
Telephone: 514.737.9701 / Toll Free: 888.275.4538
Fax: 514.342.3854 / Toll Free: 877.453.8832

12000 Biscayne Blvd., Suite #108
Miami, FL, United States 33181
Telephone: 786.600.4687 / Toll Free 844.218.8477
Fax: 786.661.4100

Email: sales@mvpgroupcorp.com

SELF CONTAINED	MODEL	O.A. LENGTH INCHES	VOLUME FT ³	CASE TEMP	ELECTRICAL - 115 VOLTS					NEMA 115V PLUG	WEIGHT LBS.		CRATE SIZE		
					COMPRESSOR			LIGHTS FANS	TOTAL AMPS		NO CRATE	WITH CRATE			
					H.P.	F.L.A.	L.R.A.						"L"	"W"	"H"
	KFM-SF-40-S	40-3/8	15.35	32/40F	3/8	8.4	43	.95	9.35	5-15P	350	512	48	44	42
	KFM-SF-50-S	52-1/8	20.22	32/40F	1/2	9.6	49	.96	10.56	5-15P	399	582	59	44	42
	KFM-SF-60-S	60	23.47	32/40F	1/2	9.6	49	1.08	10.68	5-15P	452	650	67	44	42
	KFM-SF-80-S	77-1/2	30.70	32/40F	5/8	8.9	47	1.68	10.58	5-15P	562	825	85	44	42
	KFM-SF-100-S	101-1/8	40.45	32/40F	3/4	16	64	1.81	17.81	N/A	697	974	109	44	42
	KFM-SF-120-S	117	46.95	32/40F	3/4	16	64	2.06	18.06	N/A	831	1204	124	44	42

REMOTE	MODEL	O.A. LENGTH INCHES	CASE TEMP	115 VOLTS TOTAL AMPS	B.T.U.	WEIGHT LBS.	
						NO CRATE	WITH CRATE
						KFM-SF-40-R	40-3/8
KFM-SF-50-R	52-1/8	32/40F	.51	3015	344	505	
KFM-SF-60-R	60	32/40F	.63	3159	397	571	
KFM-SF-80-R	77-1/2	32/40F	.78	4345	529	761	
KFM-SF-100-R	101-1/8	32/40F	.91	5112	642	882	
KFM-SF-120-R	117	32/40F	1.16	5472	765	1093	

NOTE

- THESE CASES ARE DESIGNED TO OPERATE USING R404A REFRIGERANT
- LENGTH INCLUDES (2) ENDS AT 1-1/2" EACH
- B.T.U.'S CALCULATED AT +14°F AND 90°F AMBIENT CASES ENGINEERED TO OPERATE AT 75°F AND 55% RH
- REMOTE CASES PROVIDED WITH EXPANSION VALVE AND LIQUID SOLENOID FOR PUMPDOWN CYCLE
- REMOTE CASES ARE HARD WIRED - NO PLUGS
- ALL CASES REQUIRE A FLOOR DRAIN

STANDARD FEATURES

- INSULATION - INJECTED FOAM
- INTERIOR - STAINLESS STEEL
- EXTERIOR - PVC COATED STEEL-SILVER
- ENDS-FOAMED BLACK POLYSTYRENE
- TILT- FORWARD TEMPERED FRONT GLASS
- CORD AND PLUG
- CASES ARE MULTIPLEXIBLE
- LED LIGHTING IN CANOPY
- REMOVABLE REAR TEMPERED GLASS SLIDING DOORS
- DEFROST AND TEMPERATURE REGULATED BY A DIGITAL CONTROLLER
- PULL-OUT CONDENSING UNIT -ON S/C ONLY
- ANTI-CONDENSATE SYSTEM FOR FRONT GLASS
- ADJUSTABLE FEET
- ETL LISTED TO UL471 AND SANITATION CLASSIFIED TO NSF7
- THESE CASES COMPLY WITH THE NATIONAL ENERGY STANDARS

OPTIONAL FEATURES

- LIFT UP FRONT GLASS
- CASTERS - ADD 4-3/8" TO HEIGHT
- ADJUSTABLE STAINLESS STEEL LEGS- FROM 5-1/8" TO 7-5/8"
- OTHER COLORS AVAILABLE
- STAINLESS STEEL EXTERIOR
- SCALE STAND WITH RECEPTACLE

WARRANTY

ONE YEAR PARTS AND LABOR WITH FOUR ADDITIONAL YEARS COMPRESSOR (PARTS ONLY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

