



## REACH-IN BOTTOM-MOUNT SERIES IB19R IB19F

### Features

- CFC free refrigerant and foam insulation
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- 3 adjustable, heavy-duty epoxy coated wire shelves per door
- Condensate heating element built into condensate pan for efficient evaporation of excess water
- Freezer door frames have integral factory installed heating element to eliminate condensation
- Easy to mount 4" casters (lockable in front) are standard with all units
- Locking doors on all units. Door swing is field reversible
- Self-closing doors that remain open at 90 degrees
- Magnetic gasket can be replaced without any tools
- Exterior: 430 stainless steel, door & front panel: 202 stainless steel
- Interior: 304 stainless steel
- Temperature IB19R: 33 to 40°F / 0.5 to 4°C
- Temperature IB19F: 0 to -10°F / -17 to -23°F
- R-290 Natural refrigerant
- Electrical: 115/60/1 with NEMA 5-15P plug, 10ft cord



NEMA  
5-15P



IB19R IB19F

### Specifications

DESIGNED TO OPERATE IN AMBIENT TEMPERATURES BETWEEN 40F-90F FOR OPTIMUM PERFORMANCE.



Model	Doors	Ext. Dimensions W X D X H (In)	Int.. Dimensions W X D X H (In)	Amps	H.P	Ship Weight
IB19R*	1	26.8 X 25.6 X 82.3	22.2 X 21.5 X 50.2	3	1/5	295 lbs
IB19F*	1	26.8 X 25.6 X 82.3	22.2 X 21.5 X 50.2	5	1/4	295 lbs

