accuc@ld

VT65ML7SSTBADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant medical grade commercial all-freezer capable of -25° C operation, with wrapped stainless steel door, towel bar handle, and lock

Highlights:

32" height for use in ADA compliant settings

24" footprint is ideally sized for any facility

Factory installed lock provides security you can count on

Product Features:

| Commercially approved | ETL-S listed to NSF-7 Standards for use in commercial establishments | |
|-------------------------------|--|--|
| Fully finished white cabinet | Allows the unit to be used freestanding | |
| Factory installed lock | Keyed lock for a secure interior | |
| Stainless steel door | Durable design with lasting elegance | |
| Professional towel bar handle | A curved handle in brushed stainless steel provides generous room for a comfortable grip | |
| -25° capable | Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials | |
| Three slide-out drawers | Conveniently organize your items while keeping the temperature stable when the door is opened | |
| Manual defrost | Static cooling system for improved temperature stability | |
| Digital thermostat | Electronic controls located in the front kickplate for easy and intuitive temperature management | |





accuc@ld

VT65ML7SSTBADA Specifications:

| Overview | | |
|---|--|--|
| Height of Cabinet | 32.0" (81 cm) | |
| Height to Hinge Cap | 32.25" (82 cm) | |
| Width | 23.63" (60 cm) | |
| Depth | 23.5" (60 cm) | |
| Depth with Handle | 24.25" (62 cm) | |
| Depth with door at 90° | 45.0" (114 cm) | |
| Capacity | 3.5 cu.ft. (99 L) | |
| Defrost Type | Manual | |
| Door | Stainless Steel | |
| Cabinet | White | |
| US Electrical Safety | UL | |
| Canadian Electrical Safety | ULC | |
| Sanitation | ETL-S | |
| Amps | 1.3 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 105.0 lbs. (48 kg) | |
| Shipping Weight | 115.0 lbs. (52 kg) | |
| Parts & Labor Warranty | 1 Year | |
| Compressor Warranty | 5 Years | |
| UPC | 761101043395 | |
| Freezer | | |
| Door Swing | RHD | |
| Reversible | Factory Reversible | |
| Crisper Finish | Opaque | |
| | | |
| Crisper Cover | Glass | |
| Crisper Cover Interior Height | Glass 24.25" (62 cm) | |
| · | | |
| Interior Height | 24.25" (62 cm) | |
| Interior Height Interior Width | 24.25" (62 cm) 17.75" (45 cm) | |
| Interior Height Interior Width Interior Depth | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) | |
| Interior Height Interior Width Interior Depth Shelf Type | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) Glass | |
| Interior Height Interior Width Interior Depth Shelf Type Thermostat Type | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) Glass Digital | |
| Interior Height Interior Width Interior Depth Shelf Type Thermostat Type Refrigerant Type | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) Glass Digital R134a | |
| Interior Height Interior Width Interior Depth Shelf Type Thermostat Type Refrigerant Type Refrigerant Amount | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) Glass Digital R134a 2.7 oz. | |
| Interior Height Interior Width Interior Depth Shelf Type Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) Glass Digital R134a 2.7 oz. 235.0 | |
| Interior Height Interior Width Interior Depth Shelf Type Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI | 24.25" (62 cm) 17.75" (45 cm) 16.5" (42 cm) Glass Digital R134a 2.7 oz. 235.0 70.0 | |

| Compressor Step Width | 17.5" (44 cm) |
|-----------------------|----------------|
| Compressor Step Depth | 5.5" (14 cm) |
| Temperature Range | -12°C to -25°C |

