






## **Drawings & Terminal Position**



ODP-AGM75/86 LEFT POSITIVE DUAL TERMINALS (SAE & SIDE)





## Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# **Charging and Self-Discharge**

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

# **Technical Data Sheet ODP-AGM75 86**

(75/86-705)

#### **Battery Type**

- With SAE posts
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

#### **Power and Performance**

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	1100
Cold Cranking Amps (CCA)	708
HCA	875
MCA	760
20Hr Nominal Capacity (Ah)	49
10Hr Nominal Capacity (Ah)	45
Reserve Capacity Minutes	89
Terminal	SAE & Side
Torque Spec	60 (6.8) side only
Internal Resistance	2.8
Short Circuit	2200

# **Dimensions and Weight**

Length	9.5 in / 241 mm
Width	6.8 in / 173 mm
Height (terminals included)	7.9 in / 201 mm
Height (container)	7.4 in / 188 mm
Weight	43.4 lbs / 19.7 kg

#### **Temperature**

Operating temperature range -40°F/-40°C to 140°F/+60°C Optimum storage temperature 68°F/+20°C

#### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016



**EnerSys World** Headquarters 2366 Bernville Road

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 Reading, PA 19605, USA 6300 Zug, Switzerland Tel: +1-800-964-2837

**EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

