





Drawings & Terminal Position



ODS-AGM16CL RIGHT POSITIVE FRONT FEMALE CONNECTION



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

Technical Data Sheet ODS-AGM16CL

(PC625)

Battery Type

- Group 16 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Up to 400 cycles at 80% depth of discharge
- Advanced dual purpose battery for engine start and deep

Power and Performance

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	540
Cold Cranking Amps (CCA)	220
HCA	400
MCA	330
20Hr Nominal Capacity (Ah)	18
10Hr Nominal Capacity (Ah)	17
Reserve Capacity Minutes	26
Terminal	M6 Receptacle
Torque Spec	40 (4.5)
Internal Resistance	7
Short Circuit	1800

Dimensions and Weight

Length	6.7 in / 170 mm
Width	3.9 in / 99 mm
Height (terminals included)	7 in / 178 mm
Height (container)	6.9 in / 175 mm
Weight	13.2 lbs / 6 kg

Temperature

Operating temperature range -40°F/-40°C to 113°F/+45°C Optimum storage temperature 68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters

2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA

EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

