




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

| Type of charging curve | IUU |
|--|----------------|
| Charger voltage at 68°F (20°C) | 14.4V to 14.8V |
| Self-discharge per month at 68°F (20°C) | 1.25% |
| Self-discharge per month at 104°F (40°C) | 5% |
| 80% depth of discharge cycles | 400 |



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library



© 2021 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. Date Downloaded: June 4, 2021

Technical Data Sheet

ODS-AGM16L

(PC680)

Battery Type

- Group 16 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Up to 400 cycles at 80% depth of discharge
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| Voltage | 12 |
|--|---------------|
| Pulse (5 second) Hot Cranking Amps (PHCA) | 520 |
| Cold Cranking Amps (CCA) | 170 |
| HCA | 350 |
| MCA | 280 |
| 20Hr Nominal Capacity (Ah) | 16 |
| 10Hr Nominal Capacity (Ah) | 16 |
| Reserve Capacity Minutes | 24 |
| Terminal | M6 Receptacle |
| Torque Spec | 50 (5.6) |
| Internal Resistance | 7 |
| Short Circuit | 1800 |
| | |

Dimensions and Weight

| Length | 7.2 in / 183 mm |
|-----------------------------|-----------------|
| Width | 3 in / 76 mm |
| Height (terminals included) | 6.4 in / 163 mm |
| Height (container) | 6.6 in / 168 mm |
| Weight | 15.4 lbs / 7 kg |

Temperature

| Operating temperature range | -40°F/-40°C to 113°F/+45°C |
|-----------------------------|----------------------------|
| Optimum storage temperature | 68°F/+20°C |

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

www.odysseybattery.com www.enersys.com