




## **Drawings & Terminal Position**



### Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# **Charging and Self-Discharge**

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

# **Technical Data Sheet ODS-AGM6M**

(PC2250)

#### **Battery Type**

- SAE tin-plated brass automotive posts & 3/8 inch threaded SS stud terminals
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

#### Power and Performance

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	2250
Cold Cranking Amps (CCA)	1225
HCA	1730
MCA	1550
20Hr Nominal Capacity (Ah)	126
10Hr Nominal Capacity (Ah)	92
Reserve Capacity Minutes	240
Terminal	SAE and 3/8-16" Stud
Torque Spec	100 (11) stud only
Internal Resistance	2.1
Short Circuit	5000

# **Dimensions and Weight**

Length	11.3 in / 287 mm
Width	10.6 in / 269 mm
Height (terminals included)	9.2 in / 234 mm
Height (container)	#REF! in / 0 mm
Weight	86 lbs / 39 kg

#### **Temperature**

Operating temperature range -40°F/-40°C to 113°F/+45°C Optimum storage temperature 68°F/+20°C

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016



**EnerSys World** Headquarters 2366 Bernville Road Reading, PA 19605, USA

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland Tel: +1-800-964-2837

**EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

