




# **Drawings & Terminal Position**



# Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).</li>
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library



© 2021 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. Date Downloaded: June 4, 2021

# **Technical Data Sheet**

# **ODS-AGM8E**

(PC310)

### **Battery Type**

- Internal threaded tin-plated brass terminals, SS M4 bolts
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

# Power and Performance

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	310
Cold Cranking Amps (CCA)	100
НСА	200
MCA	155
20Hr Nominal Capacity (Ah)	8
10Hr Nominal Capacity (Ah)	7
Reserve Capacity Minutes	9
Terminal	M4 Receptacle
Torque Spec	8.9 (1.0)
Internal Resistance	27.1
Short Circuit	455

#### **Dimensions and Weight**

Length	5.4 in / 137 mm
Width	3.4 in / 86 mm
Height (terminals included)	3.9 in / 99 mm
Height (container)	3.9 in / 99 mm
Weight	5.9 lbs / 2.7 kg

#### Temperature

Operating temperature range	-40°F/-40°C to 122°F/+50°C
Optimum storage temperature	68°F/+20°C

#### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016