




### **Drawings & Terminal Position**



## Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 68°F (20°C) without needing to charge. Recharge when the OCV is <12.6V (50% SOC).</li>
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# **Charging and Self-Discharge**

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

# Technical Data Sheet ODX-AGM65M

(NSB-AGM65M)

#### **Battery Type**

- Cycles over 900 times at 50% depth of discharge
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

#### **Power and Performance**

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	1750
Cold Cranking Amps (CCA)	930
HCA	1280
MCA	1070
20Hr Nominal Capacity (Ah)	69
10Hr Nominal Capacity (Ah)	64
Reserve Capacity Minutes	135
Terminal	М
Torque Spec	200 (22.6)/100 (11.3) studs only
Internal Resistance	3.3
Short Circuit	5000

## **Dimensions and Weight**

Length	11.8 in / 300 mm
Width	7.3 in / 185 mm
Height (terminals included)	7.6 in / 193 mm
Height (container)	6.8 in / 173 mm
Weight	54 lbs / 24.5 kg

#### **Temperature**

Operating temperature range  $-40^{\circ}\text{F}/-40^{\circ}\text{C}$  to  $176^{\circ}\text{F}/+80^{\circ}\text{C}$ Optimum storage temperature  $68^{\circ}\text{F}/+20^{\circ}\text{C}$ 

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters

2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 **EnerSys EMEA**EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

