



## **Bitcote Black Bitumen Paint** **Technical Data Sheet**

### **Description**

Bitcote is made from carefully selected Bitumens dissolved in special petroleum solvents. It provides an outstanding anti-corrosive solution for brush application on a wide range of materials, especially iron and steel. Bitcote combines easy and economical application giving anti-rust, waterproofing, flexible and durable properties. Touch dry in approximately 4-8 hours at normal temperatures with a glossy finish turning dull after a period of time due to climatic and atmospheric conditions.

### **Coverage**

1 litre of Bitcote is sufficient to cover an area of approximately 10 square meters, depending on porosity.

### **Directions**

As with all surface coatings preparation is of great importance and will influence the degree of adhesion obtained and the life of the coating. All surfaces must be sound, stable and thoroughly clean and dry. Metal surfaces should be wire brushed to remove rust. Where long term protection is required an initial treatment of a rust inhibitive product should be used. Apply by brush or spray. A minimum of two coats of Bitcote should be applied, the first being allowed to dry before the second. Apply the second coat at right angles to the first. Clean application tools with Bartoline White Spirit.

THIN WITH NO MORE THAN 10% BARTOLINE WHITE SPIRIT FOR SPRAYING.

DO NOT APPLY ORDINARY PAINTS OVER BITCOTE.

DO NOT APPLY WHERE MINERAL OILS OR SOLVENTS WILL COME INTO CONTACT.

DO NOT USE IF SURFACE TEMPERATURE CAN RISE ABOVE 70°C.

DO NOT USE ON TARMACADAM DRIVES, ROADWAYS etc.

### **Health and Safety**

See MSDS for full information.

## Technical Data

Measurement	Value	Test Method
Physical State	Liquid	Visual
Colour	Black	Visual
Odour	Distinctive hydrocarbon type	
Flash point	38 - 40°C	
VOC content	360g/l	
Density	0.91g/cm <sup>3</sup>	

## Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
1 Litre tin	40487580	5010789487584	05010789487591	6	78	468	12	6
2.5 Litre tin	40487600	5010789487607	05010789487614	6	42	252	7	6
5 Litre tin	40487530	5010789487539	05010789487539	4	36	144	9	4
20 Litre drum	40482070	5010789482077	N/A	N/A	N/A	32	16	2
205 Litre drum	40480500	N/A	N/A	N/A	N/A	4	4	1

## Customs Tariff Code

2715 0000

## Shipping Classification

Correct Shipping Name: Tars Liquid (White Spirit)  
Classification: Class 3  
UN Number: UN 1999  
Packing Group: III  
Flash Point: 39 Degrees Celsius  
Additional Information: Marine Pollutant