# **BF PRINT02 BF PRINTO2 GLOSSY**



### **PRINT&CUT**

#### PRODUCT DESCRIPTION

BF PRINT02 (matte) and BF PRINT02G (glossy) are polyurethane transparent films, printable with solvent, eco-solvent and latex inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments.

You must mirror when printing and cutting on this film.

It can be applied directly to the fabric, thus eliminating the need for any application tape.

#### **TECHNICAL DATA**

μ	
$\searrow$	

TTA

Film: PU/Polyurethane

Thickness: 50µ (±5%)

Finish: BF PRINT02 matte

Liner: adhesive PET

**BF PRINT02G glossy** 

Inks: solvent, eco-solvent, latex

#### **PLOTTER SETTING**

66

Blade: 45°

Cut settings: mirror

#### Minimum cut: 2 cm

#### APPLICATION



Temperature: 150°C - 305°F

Time: 10" Liner removal: semi-hot wait 6/7 seconds

Pressure: medium - 3,5 bar - 50 PSI

Textile: organic, synthetic, mixed

#### WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature*	40°C/104°F
Dry clean	×
Dryer	×

stTemperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

#### SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev\_2021/03



HEADOUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com www.b-flexamerica.com ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com www.b-flexpacific.com

Comply with

regulation REACH

n°1907/2006/EU

#### **APPLICATION STEPS**

- Print mirror •
- Cut 45° blade
- Weed excess material
- Turn on your heat press heat to 150°C/305°F .
- Place your graphic on the garment
- Press it 150°C/305°F for 10 seconds •
- Wait 6/7 seconds •
- Remove the liner semi-hot

#### SIZES

H 50 cm	L 25 mt / 12,5 mt / 5 mt
H 75 cm	L 25 mt
H 100 cm	L 25 mt
H 150 cm	L 25 mt

**OEKO-TEX**®

STANDARD 100 19CX00033 CENTROCOT

Tested for harmful substances ww.oeko-tex.com/standard100

Standard 100

Oeko-Tex

Class I



## **BF PRINT02-BFPRINT02 GLOSSY**

PRINT&CUT

C

- Trasparent finish; perfect on light colors
- Matte and glossy finishes available
- Soft touch